

定格総荷重表

■ 26.5 m タワー



単位:t

タワー長さ(m)	26.5								タワー長さ(m)
ジブ長さ(m)	19				22				ジブ長さ(m)
タワー角(°)	90	80	70	60	90	80	70	60	タワー角(°)
作業半径(m)									作業半径(m)
7.5	15.00				8.2 m x				7.5
8	15.00				15.00 t				8
9	15.00				15.00				9
10	15.00				15.00	15.9 m x			10
12	15.00	14.8 m x			15.00	13.90 t			12
14	15.00	15.00 t			15.00	16.9 m x			14
16	13.80	15.00	22.0 m x		13.80	13.90 t			16
18	12.00	13.00	8.65 t		11.90	12.90	23.6 m x		18
20	10.70	11.50	22.8 m x		10.50	11.30	7.80 t		20
22	21.7 m x	10.20	8.65 t	28.6 m x	9.30	10.10	24.5 m x		22
24	8.15 t	9.20	8.10	5.60 t	8.10	9.10	7.80 t	30.6 m x	24
26		8.20	7.50	29.3 m x	24.6 m x	8.20	7.30	4.95 t	26
28		26.1 m x	6.80	5.60 t	7.40 t	7.30	6.70	31.5 m x	28
30		8.10 t	6.10	5.50		29.0 m x	6.20	4.95 t	30
32			30.4 m x	5.10		6.85 t	5.70	4.90	32
34			5.95 t	4.70			33.3 m x	4.60	34
36				34.5 m x			5.35 t	4.30	36
38				4.60 t				37.4 m x	38
								4.05 t	

1. 上表に示す定格総荷重は、水平堅土上の定置荷役における値で、転倒荷重の78%以内、および移動式クレーン構造規格で定める前方安定度以上です。
2. 実際につり上げられる荷重は、上表の定格総荷重からフックなどのつり具一切の質量を差し引いた値です。
3. □太線内の値は強度に基づいています。
4. 作業半径とは、荷をつった状態での旋回中心からつり荷の重心までの水平距離です。
5. カウンタウエイトは、31.7t（標準仕様）、ロアウエイトは7.5t（標準仕様）です。
6. 表中の○○ m x ○○ t は、作業半径 m x 定格総荷重 t を示します。
7. 使用するフックは、以下の通りです。
 2本掛・・・35t フック（フック質量 0.90t）
 1本掛・・・12t フック（フック質量 0.51t）
8. タワーブームにスカイウォークが取り付け付いた状態で作業する場合の定格総荷重は、上表の定格総荷重から下表の値を差し引いた値となります。

タワー長さ	26.5m	29.5m	32.5m	35.5m	38.5m	41.5m	44.5m
差引き荷重	0.1t	0.1t	0.1t	0.2t	0.2t	0.2t	0.2t

■ 29.5 m タワー



タワー長さ(m)		29.5								タワー長さ(m)	
ジブ長さ(m)		19				22				ジブ長さ(m)	
タワー角(°)										タワー角(°)	
作業半径(m)		90	80	70	60	90	80	70	60	作業半径(m)	
7.5	15.00					8.2 m x				7.5	
8	15.00					15.00 t				8	
9	15.00					15.00				9	
10	15.00					15.00	16.4 m x			10	
12	15.00	15.3 m x				15.00	13.15 t			12	
14	15.00	16.2 m x				15.00	17.4 m x			14	
16	13.80	14.60 t	23.0 m x			13.80	13.15 t			16	
18	12.00	12.80	7.85 t			11.90	12.70	24.6 m x		18	
20	10.50	11.30	23.8 m x			10.50	11.10	7.00 t		20	
22	21.7 m x	10.00	7.85 t			9.30	9.90	25.6 m x		22	
24	8.15 t	9.00	7.80	30.1 m x		8.10	8.90	7.00 t		24	
26		8.00	7.20	4.85 t		24.6 m x	8.10	6.90	32.1 m x	26	
28		26.6 m x	6.50	30.8 m x		7.60 t	7.40	6.40	4.30 t	28	
30		7.65 t	6.00	4.85 t			29.5 m x	5.90	33.0 m x	30	
32			31.5 m x	4.70			6.85 t	5.40	4.30 t	32	
34			5.60 t	4.40				4.90	4.20	34	
36				4.10				34.4 m x	4.00	36	
38								4.75 t	3.80	38	
40									38.9 m x	40	
									3.65 t		

タワー長さ(m)		29.5				タワー長さ(m)	
ジブ長さ(m)		25				ジブ長さ(m)	
タワー角(°)						タワー角(°)	
作業半径(m)		90	80	70	60	作業半径(m)	
7.5	8.8 m x					7.5	
8	15.00 t					8	
9	15.00					9	
10	15.00					10	
12	15.00	17.5 m x				12	
14	15.00	11.70 t				14	
16	13.70	18.7 m x				16	
18	11.90	11.70 t				18	
20	10.40	11.00	26.2 m x			20	
22	9.30	9.90	6.30 t			22	
24	8.40	8.90	27.3 m x			24	
26	7.60	8.05	6.30 t			26	
28	27.5 m x	7.30	6.20	34.2 m x		28	
30	6.25 t	6.70	5.80	3.85 t		30	
32		6.15	5.35	35.1 m x		32	
34		32.4 m x	4.95	3.85 t		34	
36		6.05 t	4.60	3.80		36	
38			37.3 m x	3.60		38	
40			4.30 t	3.40		40	
42				41.8 m x		42	
				3.20 t			

・注意事項は、51 ページを参照してください。

■ 32.5 m タワー



タワー長さ(m) ジブ長さ(m) タワー角(°) 作業半径(m)	32.5								タワー長さ(m) ジブ長さ(m) タワー角(°) 作業半径(m)
	19				22				
	90	80	70	60	90	80	70	60	
7.6	15.00				8.2 m x 15.00 t				7.6
8	15.00				15.00				8
9	15.00				15.00				9
10	15.00	15.8 m x 13.45 t			15.00				10
12	15.00				15.00				12
14	15.00	16.7 m x 13.45 t			15.00	16.9 m x 12.40 t			14
16	13.90				13.80	12.40 t			16
18	12.00	12.50	24.1 m x 6.95 t		12.00	12.40			18
20	10.50	11.00			10.50	10.90	25.7 m x 6.25 t		20
22	21.8 m x 8.55 t	9.80	24.9 m x 6.95 t		9.30	9.70			22
24		8.80	6.70		8.10	8.70	26.6 m x 6.25 t		24
26		8.00		31.6 m x 4.30 t	24.7 m x 7.65 t	7.90			26
28		27.1 m x 7.55 t	6.20		7.20	6.00	33.6 m x 3.75 t		28
30			5.70	32.3 m x 4.30 t		6.50			30
32			5.20				5.20	34.5 m x 3.75 t	32
34			32.5 m x 5.05 t	4.00			4.80		34
36				3.70			35.4 m x 4.50 t	3.60	36
38				37.5 m x 3.45 t				3.40	38
40								3.20	40
42								40.4 m x 3.15 t	42
44									44

単位:t

タワー長さ(m) ジブ長さ(m) タワー角(°) 作業半径(m)	32.5								タワー長さ(m) ジブ長さ(m) タワー角(°) 作業半径(m)
	25				28				
	90	80	70	60	90	80	70	60	
7.6	8.9 m x 15.00 t				9.5 m x 15.00 t				7.6
8	15.00				15.00				8
9	15.00				15.00				9
10	15.00				15.00				10
12	15.00	18.1 m x 11.20 t			15.00				12
14	15.00				15.00	19.2 m x 10.10 t			14
16	13.80	19.2 m x 11.20 t			13.70	10.10 t			16
18	11.90				11.80	20.5 m x 10.10 t			18
20	10.50	10.80			10.40				20
22	9.30	9.70	27.2 m x 5.80 t		9.20	9.50			22
24	8.40	8.75			8.30	8.65			24
26	7.60	7.90	28.3 m x 5.80 t		7.50	7.80	28.8 m x 5.30 t		26
28	27.6 m x 6.20 t	7.20			6.90	7.10			28
30		6.55	5.50	35.7 m x 3.40 t	6.10	6.50	5.30		30
32		6.05	5.10		30.5 m x 5.60 t	5.95	5.00	37.7 m x 3.10 t	32
34		32.9 m x 5.80 t	4.70	36.6 m x 3.40 t		5.50	4.60		34
36			4.40			35.8 m x 5.15 t	4.30	38.7 m x 3.10 t	36
38			4.05	3.30			4.00		38
40			38.3 m x 4.00 t	3.10			3.70	3.00	40
42				2.90			41.2 m x 3.50 t	2.80	42
44				43.3 m x 2.75 t				2.60	44
46								2.40	46
48								46.2 m x 2.35 t	48

単位:t

・注意事項は、51 ページを参照してください。

■ 35.5 m タワー



単位:t

タワー長さ(m)	35.5								タワー長さ(m)
ジブ長さ(m)	19				22				ジブ長さ(m)
タワー角(°)	90	80	70	60	90	80	70	60	タワー角(°)
作業半径(m)									作業半径(m)
7.6	15.00				8.2 m x				7.6
8	15.00				15.00 t				8
9	15.00				15.00				9
10	15.00	16.3 m x			15.00				10
12	15.00	13.00 t			15.00	17.5 m x			12
14	15.00	17.2 m x			15.00	11.55 t			14
16	14.00	13.00 t			13.90	18.5 m x			16
18	12.10	12.40			12.10	11.55 t			18
20	10.60	10.90			10.60	10.80	26.7 m x		20
22	21.8 m x	9.80	25.1 m x		9.50	9.75	5.85 t		22
24	8.65 t	8.80	6.50 t		8.40	8.75	27.6 m x		24
26		8.00	6.50		24.7 m x	7.90	5.85 t		26
28		27.6 m x	6.10		7.05 t	7.20	5.80		28
30		7.35 t	5.60	33.1 m x		6.60	5.50		30
32			5.10	3.80 t		30.5 m x	5.00	35.1 m x	32
34			33.5 m x	3.80		6.40 t	4.70	3.40 t	34
36			4.70 t	3.60			4.35	3.40	36
38				3.40			36.4 m x	3.20	38
40				39.0 m x			4.30 t	3.00	40
42				3.30 t				41.9 m x	42
44								2.80 t	44

タワー長さ(m)	35.5								タワー長さ(m)
ジブ長さ(m)	25				28				ジブ長さ(m)
タワー角(°)	90	80	70	60	90	80	70	60	タワー角(°)
作業半径(m)									作業半径(m)
7.6	8.9 m x								7.6
8	15.00 t				9.5 m x				8
9	15.00				15.00 t				9
10	15.00				15.00				10
12	15.00	18.6 m x			15.00				12
14	15.00	10.80 t			15.00	19.7 m x			14
16	13.90	19.8 m x			13.80	9.80 t			16
18	12.00	10.80 t			11.90	21.0 m x			18
20	10.60	10.70			10.50	9.80 t			20
22	9.40	9.60	28.3 m x		9.40	9.40			22
24	8.50	8.60	5.40 t		8.40	8.50	29.9 m x		24
26	7.70	7.75	29.3 m x		7.60	7.70	4.75 t		26
28	27.6 m x	7.05	5.40 t		7.00	7.00	31.1 m x		28
30	6.25 t	6.45	5.30		6.15	6.40	4.75 t		30
32		5.95	4.95	37.2 m x	30.5 m x	5.85	4.70		32
34		33.4 m x	4.55	3.05 t	5.65 t	5.40	4.45	39.2 m x	34
36		5.60 t	4.20	38.1 m x		5.00	4.10	2.65 t	36
38			3.90	3.05 t		36.3 m x	3.80	40.2 m x	38
40			39.3 m x	2.90		4.95 t	3.55	2.65 t	40
42			3.75 t	2.70			3.30	2.50	42
44				2.50			42.2 m x	2.30	44
46				44.8 m x			3.25 t	2.10	46
48				2.40 t				47.7 m x	48
								1.90 t	

タワー長さ(m)	35.5				タワー長さ(m)
ジブ長さ(m)	31				ジブ長さ(m)
タワー角(°)	90	80	70	60	タワー角(°)
作業半径(m)					作業半径(m)
10	10.2 m x				10
	13.50 t				
12	13.50				12
14	13.50				14
16	13.50	20.8 m x			16
18	11.90	9.15 t			18
20	10.40	22.3 m x			20
22	9.30	9.15 t			22
24	8.40	8.40			24
26	7.60	7.55	31.5 m x		26
28	6.90	6.85	4.40 t		28
30	6.40	6.30	32.8 m x		30
32	5.90	5.75	4.40 t		32
34	33.4 m x	5.30	4.30		34
36	4.80 t	4.90	4.00	41.2 m x	36
38		4.55	3.70	2.25 t	38
40		39.2 m x	3.45	42.3 m x	40
42		4.40 t	3.20	2.25 t	42
44			3.00	2.10	44
46			45.1 m x	2.00	46
48			2.85 t	1.90	48
50				1.80	50
52				50.6 m x	52
				1.75 t	

・ 注意事項は、51ページを参照してください。

■ 38.5 m タワー



単位:t

タワー長さ(m)		38.5								タワー長さ(m)	
ジブ長さ(m)	19				22				ジブ長さ(m)		
タワー角(°)	90	80	70	60	90	80	70	60	タワー角(°)		
作業半径(m)	90	80	70	60	90	80	70	60	作業半径(m)		
7.6	15.00				8.3 m x				7.6		
8	15.00				15.00 t				8		
9	15.00				15.00				9		
10	15.00	16.9 m x			15.00				10		
12	15.00	12.40 t			15.00	18.0 m x			12		
14	15.00	17.7 m x			15.00	11.15 t			14		
16	14.00	12.40 t			14.00	19.0 m x			16		
18	12.10	12.20			12.10	11.15 t			18		
20	10.70	10.70	26.1 m x		10.60	10.60			20		
22	21.8 m x	9.50	5.75 t		9.50	9.50	27.7 m x		22		
24	8.85 t	8.60	26.9 m x		8.40	8.60	5.10 t		24		
26		7.80	5.75 t		24.7 m x	7.75	28.6 m x		26		
28		7.00	5.60	34.6 m x	7.15 t	7.05	5.10 t		28		
30		28.1 m x	5.30	3.15 t		6.45	5.00	36.6 m x	30		
32		6.95 t	4.90	35.3 m x		31.0 m x	4.80	2.75 t	32		
34			4.50	3.15 t		6.20 t	4.40	37.5 m x	34		
36			34.5 m x	3.10			4.10	2.75 t	36		
38			4.40 t	2.90			37.4 m x	2.70	38		
40				2.70			3.85 t	2.50	40		
42				40.5 m x				2.30	42		
44				2.65 t				43.4 m x	44		
46								2.15 t	46		

タワー長さ(m)		38.5								タワー長さ(m)	
ジブ長さ(m)	25				28				ジブ長さ(m)		
タワー角(°)	90	80	70	60	90	80	70	60	タワー角(°)		
作業半径(m)	90	80	70	60	90	80	70	60	作業半径(m)		
7.6	8.9 m x				9.6 m x				7.6		
8	15.00 t				15.00 t				8		
9	15.00				15.00				9		
10	15.00				15.00				10		
12	15.00				15.00				12		
14	15.00	19.1 m x			15.00	20.2 m x			14		
16	13.90	10.30 t			13.80	9.40 t			16		
18	12.00	20.3 m x			12.00	21.5 m x			18		
20	10.60	10.30 t			10.50	9.40 t			20		
22	9.40	9.40			9.40	9.20			22		
24	8.50	8.45	29.3 m x		8.40	8.35			24		
26	7.70	7.60	4.90 t		7.60	7.55	30.9 m x		26		
28	27.6 m x	6.95	30.4 m x		7.00	6.85	4.45 t		28		
30	6.35 t	6.35	4.90 t		6.25	6.25	32.1 m x		30		
32		5.80	4.60		30.5 m x	5.75	4.45 t		32		
34		33.9 m x	4.30		5.75 t	5.30	4.20		34		
36		5.40 t	4.00	38.7 m x		4.90	3.90		36		
38			3.70	2.40 t		36.8 m x	3.60	40.7 m x	38		
40			3.40	2.40		4.75 t	3.35	2.00 t	40		
42			40.3 m x	2.20			3.10	2.00	42		
44			3.35 t	2.20			43.2 m x	1.70	44		
46				1.80			3.00 t	1.40	46		
48				46.3 m x					48		
				1.75 t							

タワー長さ(m)		38.5						タワー長さ(m)	
ジブ長さ(m)	31			34			ジブ長さ(m)		
タワー角(°)	90	80	70	90	80	70	タワー角(°)		
作業半径(m)	90	80	70	90	80	70	作業半径(m)		
	10.2 m x			10.9 m x					
10	13.50 t			11.50 t			10		
12	13.50			11.50			12		
14	13.50			11.50			14		
16	13.50	21.4 m x		11.50			16		
18	11.90	8.60 t		11.50	22.5 m x		18		
20	10.50	22.8 m x		10.40	8.05 t		20		
22	9.30	8.60 t		9.30	24.1 m x		22		
24	8.40	8.20		8.30	8.05 t		24		
26	7.60	7.40		7.50	7.30		26		
28	6.90	6.75		6.90	6.60	34.1 m x	28		
30	6.40	6.15	32.5 m x	6.30	6.00	3.70 t	30		
32	5.90	5.65	4.10 t	5.80	5.50	35.5 m x	32		
34	33.4 m x	5.20	4.10	5.40	5.05	3.70 t	34		
36	4.85 t	4.80	3.80	4.50	4.65	3.65	36		
38		4.45	3.50	36.3 m x	4.35	3.35	38		
40		39.7 m x	3.25	4.25 t	4.05	3.10	40		
42		4.20 t	3.00		3.75	2.85	42		
44			2.80		42.6 m x	2.65	44		
46			2.60		3.70 t	2.45	46		
48			46.1 m x			2.30	48		
50			2.60 t			49.0 m x	50		
						2.25 t			

・注意事項は、
51 ページを参照
してください。

■ 41.5 m タワー



単位:t

タワー長さ(m)	41.5								タワー長さ(m)
ジブ長さ(m)	19				22				ジブ長さ(m)
タワー角(°)	90	80	70	60	90	80	70	60	タワー角(°)
作業半径(m)	90	80	70	60	90	80	70	60	作業半径(m)
7.6	15.00				8.3 m x				7.6
8	15.00				15.00 t				8
9	15.00				15.00				9
10	15.00				15.00				10
12	15.00	17.4 m x			15.00	18.5 m x			12
14	15.00	11.65 t			15.00	10.65 t			14
16	14.00	18.3 m x			14.00	19.5 m x			16
18	12.10	11.65 t			12.10	10.65 t			18
20	10.70	10.50			10.60	10.40			20
22	21.8 m x	9.30			9.50	9.30	28.7 m x		22
24	9.05 t	8.40	27.1 m x		8.40	8.40	4.95 t		24
26		7.60	5.40 t		24.7 m x	7.60	29.7 m x		26
28		6.80	5.40		7.25 t	6.95	4.95 t		28
30		28.7 m x	5.00	36.1 m x		6.35	4.90		30
32		6.50 t	4.60	2.95 t		31.6 m x	4.50	38.1 m x	32
34			4.30	36.8 m x		5.90 t	4.20	2.50 t	34
36			35.6 m x	2.95 t			3.90	39.0 m x	36
38			4.05 t	2.80			3.60	2.50 t	38
40				2.60			38.5 m x	2.40	40
42				2.40			3.50 t	2.20	42
44								2.00	44
46								44.9 m x	46
								1.90 t	

単位:t

タワー長さ(m)	41.5						タワー長さ(m)
ジブ長さ(m)	25			28			ジブ長さ(m)
タワー角(°)	90	80	70	90	80	70	タワー角(°)
作業半径(m)	90	80	70	90	80	70	作業半径(m)
7.6	8.9 m x						7.6
8	15.00 t			9.6 m x			8
9	15.00			15.00 t			9
10	15.00			15.00			10
12	15.00			15.00			12
14	15.00	19.6 m x		15.00			14
16	13.90	9.55 t		13.80	20.7 m x		16
18	12.00	20.8 m x		12.00	8.95 t		18
20	10.60	9.55 t		10.50	22.1 m x		20
22	9.40	9.10		9.40	8.95 t		22
24	8.50	8.30	30.3 m x	8.40	8.20		24
26	7.70	7.50	4.45 t	7.60	7.40	31.9 m x	26
28	27.6 m x	6.80	31.4 m x	7.00	6.70	4.10 t	28
30	6.45 t	6.20	4.45 t	6.30	6.10	33.1 m x	30
32		5.70	4.40	30.5 m x	5.60	4.10 t	32
34		5.25	4.10	5.85 t	5.20	4.00	34
36		34.5 m x	3.80		4.80	3.70	36
38		5.15 t	3.50		37.4 m x	3.40	38
40			3.25		4.55 t	3.15	40
42			41.4 m x			2.95	42
44			3.10 t			2.75	44
46						44.3 m x	46
						2.70 t	

・注意事項は、51 ページを参照してください。

■ 41.5 m タワー



単位:t

タワー長さ(m)	41.5						タワー長さ(m)
ジブ長さ(m)	31			34			ジブ長さ(m)
タワー角(°)	90	80	70	90	80	70	タワー角(°)
作業半径(m)	90	80	70	90	80	70	作業半径(m)
10	10.2 m x 13.50 t			10.9 m x 11.50 t			10
12	13.50			11.50			12
14	13.50			11.50			14
16	13.50	21.9 m x		11.50			16
18	11.90	8.20 t		11.50	23.0 m x		18
20	10.50	23.3 m x		10.40	7.45 t		20
22	9.30	8.20 t		9.30	24.6 m x		22
24	8.40	8.00		8.30	7.45 t		24
26	7.60	7.25		7.50	7.10		26
28	6.90	6.60	33.5 m x	6.90	6.45		28
30	6.40	6.00	3.75 t	6.30	5.90	35.1 m x	30
32	5.90	5.50	34.8 m x	5.80	5.40	3.30 t	32
34	33.4 m x	5.10	3.75 t	5.40	4.95	36.6 m x	34
36	4.90 t	4.70	3.60	4.55	4.55	3.30 t	36
38		4.35	3.30	36.3 m x	4.25	3.15	38
40		4.05	3.05	4.30 t	3.95	2.90	40
42		40.3 m x	2.80		3.65	2.70	42
44		4.00 t	2.60		43.1 m x	2.50	44
46			2.45		3.55 t	2.30	46
48			47.2 m x			2.15	48
50			2.35 t			2.00	50
52						50.1 m x	52
54						1.95 t	54

単位:t

タワー長さ(m)	41.5			タワー長さ(m)
ジブ長さ(m)	37			ジブ長さ(m)
タワー角(°)	90	80	70	タワー角(°)
作業半径(m)	90	80	70	作業半径(m)
10	11.5 m x 9.50 t			10
12	9.50			12
14	9.50			14
16	9.50			16
18	9.50	24.1 m x		18
20	9.30	7.05 t		20
22	8.90	25.9 m x		22
24	8.40	7.05 t		24
26	7.60	7.00		26
28	6.90	6.35		28
30	6.40	5.75		30
32	5.90	5.25	36.7 m x	32
34	5.40	4.85	3.00 t	34
36	5.10	4.45	38.3 m x	36
38	4.60	4.10	3.00 t	38
40	39.2 m x	3.80	2.80	40
42	3.70 t	3.55	2.55	42
44		3.30	2.35	44
46		3.10	2.20	46
48			2.00	48
50			1.85	50
52			1.70	52
54			53.0 m x 1.65 t	54

・注意事項は、51 ページを参照してください。

■ 44.5 m タワー



単位:t

タワー長さ(m) ジブ長さ(m) タワー角(°) 作業半径(m)	44.5						タワー長さ(m) ジブ長さ(m) タワー角(°) 作業半径(m)
	19			22			
	90	80	70	60	90	80	70
7.7	15.00				8.3 m x		7.7
8	15.00				15.00 t		8
9	15.00				15.00		9
10	15.00				15.00		10
12	15.00	17.9 m x			15.00		12
14	15.00	10.90 t			15.00	19.0 m x	14
16	14.00	18.8 m x			14.00	10.05 t	16
18	12.10	10.90 t			12.10	20.1 m x	18
20	10.70	10.30			10.60	10.05 t	20
22	21.9 m x	9.30	28.2 m x		9.50	9.10	22
24	8.85 t	8.30	4.85 t		8.40	8.20	24
26		7.60	29.0 m x		24.8 m x	7.50	29.8 m x
28		6.90	4.85 t		7.10 t	6.80	4.35 t
30		29.2 m x	4.70			6.20	30.7 m x
32		6.45 t	4.40	37.6 m x		5.70	4.35 t
34			4.00	2.45 t		32.1 m x	4.20
36			3.60	38.3 m x		5.70 t	3.90
38			36.6 m x	2.45 t			3.60
40			3.45 t	2.30			3.40
42				2.10			39.5 m x
44				43.5 m x			3.25 t
46				1.90 t			42
							44
							46

単位:t

タワー長さ(m) ジブ長さ(m) タワー角(°) 作業半径(m)	44.5						タワー長さ(m) ジブ長さ(m) タワー角(°) 作業半径(m)
	25			28			
	90	80	70	90	80	70	
8				9.6 m x			8
9	15.00			15.00 t			9
10	15.00			15.00			10
12	15.00			15.00			12
14	15.00	20.1 m x		15.00			14
16	13.90	9.15 t		13.70	21.3 m x		16
18	12.10	21.3 m x		12.00	8.30 t		18
20	10.60	9.15 t		10.50	22.6 m x		20
22	9.40	8.90		9.40	8.30 t		22
24	8.50	8.10		8.40	7.90		24
26	7.70	7.35	31.4 m x	7.70	7.25		26
28	27.7 m x	6.65	4.00 t	7.00	6.55	32.9 m x	28
30	6.40 t	6.10	32.4 m x	6.30	6.00	3.65 t	30
32		5.60	4.00 t	30.6 m x	5.50	34.1 m x	32
34		5.15	3.80	5.85 t	5.05	3.65 t	34
36		35.0 m x	3.60		4.70	3.40	36
38		4.95 t	3.30		37.9 m x	3.20	38
40			3.10		4.35 t	3.00	40
42			2.85			2.75	42
44			42.4 m x			2.50	44
46			2.80 t			45.3 m x	46
						2.30 t	

・注意事項は、51 ページを参照してください。

■ 44.5 m タワー



単位:t

タワー長さ(m)	44.5						タワー長さ(m)
ジブ長さ(m)	31			34			ジブ長さ(m)
タワー角(°)	90	80	70	90	80	70	タワー角(°)
作業半径(m)							作業半径(m)
10	10.3 m x 13.50 t			10.9 m x 11.50 t			10
12	13.50			11.50			12
14	13.50			11.50			14
16	12.85			11.50			16
18	11.90			11.35	23.5 m x		18
20	10.50	22.4 m x		10.40	7.05 t		20
22	9.30	7.80 t		9.30	25.1 m x		22
24	8.40	7.80		8.30	7.05 t		24
26	7.60	7.15		7.50	6.90		26
28	6.90	6.45		6.90	6.30		28
30	6.40	5.90		6.30	5.75		30
32	5.90	5.40	34.5 m x	5.80	5.25		32
34	33.5 m x	4.95	3.30 t	5.40	4.85	36.1 m x	34
36	4.85 t	4.60	3.30	4.60	4.45	2.90 t	36
38		4.25	3.10	36.4 m x	4.10	2.90	38
40		3.95	2.85	4.30 t	3.80	2.70	40
42		40.8 m x	2.60		3.55	2.50	42
44		3.85 t	2.40		43.7 m x	2.30	44
46			2.30		3.35 t	2.15	46
48			2.10			1.95	48
50			48.2 m x			1.80	50
52			2.10 t			51.1 m x 1.65 t	52

単位:t

タワー長さ(m)	44.5			タワー長さ(m)
ジブ長さ(m)	37			ジブ長さ(m)
タワー角(°)	90	80	70	タワー角(°)
作業半径(m)				作業半径(m)
10	11.6 m x 9.50 t			10
12	9.50			12
14	9.50			14
16	9.50			16
18	9.50			18
20	9.20	24.6 m x		20
22	8.90	6.75 t		22
24	8.40	26.4 m x		24
26	7.60	6.75 t		26
28	6.90	6.20		28
30	6.40	5.65		30
32	5.90	5.15	37.7 m x	32
34	5.50	4.70	2.55 t	34
36	5.10	4.35	39.3 m x	36
38	4.65	4.00	2.55 t	38
40	39.3 m x	3.70	2.50	40
42	3.70 t	3.45	2.30	42
44		3.20	2.15	44
46		3.00	2.00	46
48		46.6 m x	1.80	48
50		2.95 t	1.60	50
52			1.40	52

・注意事項は、51 ページを参照してください。