

■ブーム定格総荷重表

					
MB			6.6m	360°	JPN

	m	9.35	16.4	23.45	30.5	m
	2.5	25.00	18.00	12.50		2.5
	3.0	25.00	18.00	12.50		3.0
	3.5	25.00	18.00	12.50	8.00	3.5
	4.0	23.50	18.00	12.50	8.00	4.0
	4.5	21.50	18.00	12.50	8.00	4.5
	5.0	19.60	18.00	12.50	8.00	5.0
	5.5	17.80	17.00	12.50	8.00	5.5
	6.0	16.30	16.00	12.50	8.00	6.0
	6.5	15.10	15.00	12.25	8.00	6.5
	7.0		14.00	11.50	8.00	7.0
	8.0		11.40	10.20	8.00	8.0
	9.0		9.30	9.00	8.00	9.0
	10.0		7.80	7.60	7.15	10.0
	11.0		6.50	6.65	6.40	11.0
	12.0		5.55	5.80	5.60	12.0
	13.0		4.75	5.00	4.90	13.0
	13.5		4.45	4.65	4.60	13.5
	14.0			4.35	4.40	14.0
	15.0			3.85	3.90	15.0
	16.0			3.40	3.45	16.0
	17.0			3.00	3.05	17.0
	18.0			2.65	2.70	18.0
	19.0			2.35	2.40	19.0
	20.0			2.10	2.15	20.0
	20.5			2.00	2.05	20.5
	21.0				1.95	21.0
	22.0				1.75	22.0
	24.0				1.40	24.0
	26.0				1.10	26.0
	27.9				0.90	27.9
	1	0	33	66	100	1
	2	0	33	66	100	2
	3	0	33	66	100	3
	ID	1	1	1	1	ID
	[DEG]	0~84	0~84	0~84	0~84	[DEG]
		8	6	4	4	
		25t	25t	25t	25t	

					
MB			6.1m	360°	JPN

	m	9.35	16.4	23.45	30.5	m
	2.5	25.00	18.00	12.50		2.5
	3.0	25.00	18.00	12.50		3.0
	3.5	25.00	18.00	12.50	8.00	3.5
	4.0	23.50	18.00	12.50	8.00	4.0
	4.5	21.50	18.00	12.50	8.00	4.5
	5.0	19.60	18.00	12.50	8.00	5.0
	5.5	17.80	17.00	12.50	8.00	5.5
	6.0	16.30	16.00	12.50	8.00	6.0
	6.5	15.00	15.00	12.25	8.00	6.5
	7.0		13.50	11.50	8.00	7.0
	8.0		10.45	10.20	8.00	8.0
	9.0		8.35	8.60	8.00	9.0
	10.0		6.85	7.10	7.10	10.0
	11.0		5.75	6.00	6.00	11.0
	12.0		4.90	5.10	5.15	12.0
	13.0		4.20	4.40	4.45	13.0
	13.5		3.90	4.10	4.15	13.5
	14.0			3.80	3.90	14.0
	15.0			3.35	3.40	15.0
	16.0			2.95	3.00	16.0
	17.0			2.60	2.65	17.0
	18.0			2.30	2.35	18.0
	19.0			2.05	2.10	19.0
	20.0			1.85	1.85	20.0
	20.5			1.75	1.75	20.5
	21.0				1.65	21.0
	22.0				1.50	22.0
	24.0				1.20	24.0
	26.0				0.95	26.0
	27.8				0.75	27.8
	1	0	33	66	100	1
	2	0	33	66	100	2
	3	0	33	66	100	3
	ID	1	1	1	1	ID
	[DEG]	0~84	0~84	0~84	0~84	[DEG]
		8	6	4	4	
		25t	25t	25t	25t	

					
MB			5.0m	360°	JPN

	m	9.35	16.4	23.45	30.5	m
	2.5	25.00	18.00	12.50		2.5
	3.0	25.00	18.00	12.50		3.0
	3.5	25.00	18.00	12.50	8.00	3.5
	4.0	23.50	18.00	12.50	8.00	4.0
	4.5	21.20	18.00	12.50	8.00	4.5
	5.0	18.00	18.00	12.50	8.00	5.0
	5.5	14.60	15.10	12.50	8.00	5.5
	6.0	12.20	12.80	12.50	8.00	6.0
	6.5	10.35	11.00	11.25	8.00	6.5
	7.0		9.65	9.85	8.00	7.0
	8.0		7.50	7.75	7.60	8.0
	9.0		6.05	6.25	6.40	9.0
	10.0		4.95	5.15	5.30	10.0
	11.0		4.15	4.35	4.45	11.0
	12.0		3.50	3.70	3.80	12.0
	13.0		3.00	3.15	3.25	13.0
	13.5		2.80	2.90	3.00	13.5
	14.0			2.70	2.80	14.0
	15.0			2.35	2.40	15.0
	16.0			2.05	2.10	16.0
	17.0			1.75	1.85	17.0
	18.0			1.55	1.60	18.0
	19.0			1.35	1.40	19.0
	20.0			1.20	1.20	20.0
	20.5			1.10	1.10	20.5
	21.0				1.05	21.0
	22.0				0.90	22.0
	24.0				0.65	24.0
	26.0					26.0
	27.8					27.8
	1	0	33	66	100	1
	2	0	33	66	100	2
	3	0	33	66	100	3
	ID	1	1	1	1	ID
	[DEG]	0~84	0~84	0~84	33~84	[DEG]
		8	6	4	4	
		25t	25t	25t	25t	

					
MB			3.6m	360°	JPN

	m	9.35	16.4	23.45	30.5	m
	2.5	25.00	18.00	12.50		2.5
	3.0	25.00	18.00	12.50		3.0
	3.5	20.00	18.00	12.50	8.00	3.5
	4.0	15.40	16.00	12.50	8.00	4.0
	4.5	12.10	12.90	12.50	8.00	4.5
	5.0	9.90	10.65	10.80	8.00	5.0
	5.5	8.25	8.95	9.20	8.00	5.5
	6.0	7.00	7.65	7.95	8.00	6.0
	6.5	6.00	6.60	6.90	6.80	6.5
	7.0		5.75	6.05	6.00	7.0
	8.0		4.50	4.75	4.75	8.0
	9.0		3.60	3.80	3.90	9.0
	10.0		2.90	3.10	3.20	10.0
	11.0		2.40	2.55	2.65	11.0
	12.0		1.95	2.10	2.20	12.0
	13.0		1.60	1.75	1.85	13.0
	13.5		1.45	1.60	1.70	13.5
	14.0			1.45	1.55	14.0
	15.0			1.20	1.30	15.0
	16.0			1.00	1.05	16.0
	17.0			0.80	0.85	17.0
	18.0			0.65	0.70	18.0
	19.0			0.50	0.55	19.0
	20.0					20.0
	20.5					20.5
	21.0					21.0
	22.0					22.0
	24.0					24.0
	26.0					26.0
	27.8					27.8
	1	0	33	66	100	1
	2	0	33	66	100	2
	3	0	33	66	100	3
	ID	1	1	1	1	ID
	[DEG]	0~84	0~84	26~84	48~84	[DEG]
		8	6	4	4	
		25t	25t	25t	25t	

					
MB			(X型) 3.1m	360°	JPN

	m	9.35	16.4	23.45	30.5	m
	2.5	18.00	16.00	12.50		2.5
	3.0	18.00	16.00	12.50		3.0
	3.5	14.50	16.00	12.50	8.00	3.5
	4.0	11.60	12.00	12.50	8.00	4.0
	4.5	9.30	10.00	10.20	8.00	4.5
	5.0	7.60	8.40	8.60	8.00	5.0
	5.5	6.40	7.10	7.30	7.30	5.5
	6.0	5.40	6.10	6.30	6.30	6.0
	6.5	4.70	5.30	5.50	5.50	6.5
	7.0		4.60	4.85	4.90	7.0
	8.0		3.60	3.80	3.80	8.0
	9.0		2.80	3.05	3.05	9.0
	10.0		2.30	2.45	2.50	10.0
	11.0		1.80	2.00	2.05	11.0
	12.0		1.50	1.60	1.65	12.0
	13.0		1.20	1.30	1.35	13.0
	13.5		1.00	1.20	1.25	13.5
	14.0			1.05	1.10	14.0
	15.0			0.85	0.90	15.0
	16.0			0.65	0.70	16.0
	17.0			0.50	0.55	17.0
	18.0					18.0
	19.0					19.0
	20.0					20.0
	20.5					20.5
	21.0					21.0
	22.0					22.0
	24.0					24.0
	26.0					26.0
	27.8					27.8
	1	0	33	66	100	1
	2	0	33	66	100	2
	3	0	33	66	100	3
	ID	1	1	1	1	ID
	[DEG]	0~84	0~84	37~84	53~84	[DEG]
		6	6	4	4	
		25t	25t	25t	25t	

					
MB			(H型) 2.3m	360°	JPN

	m	9.35	16.4	23.45	30.5	m
	2.5	12.20	12.00	10.00		2.5
	3.0	12.20	12.00	10.00		3.0
	3.5	9.75	10.00	10.00	6.00	3.5
	4.0	7.60	8.00	8.50	6.00	4.0
	4.5	6.10	6.70	7.00	6.00	4.5
	5.0	5.00	5.50	5.80	5.80	5.0
	5.5	4.10	4.60	4.90	5.00	5.5
	6.0	3.45	4.00	4.25	4.35	6.0
	6.5	2.90	3.40	3.65	3.75	6.5
	7.0		2.95	3.15	3.30	7.0
	8.0		2.25	2.50	2.55	8.0
	9.0		1.70	1.90	2.00	9.0
	10.0		1.30	1.50	1.55	10.0
	11.0		0.95	1.15	1.20	11.0
	12.0		0.70	0.85	0.90	12.0
	13.0					13.0
	13.5					13.5
	14.0					14.0
	15.0					15.0
	16.0					16.0
	17.0					17.0
	18.0					18.0
	19.0					19.0
	20.0					20.0
	20.5					20.5
	21.0					21.0
	22.0					22.0
	24.0					24.0
	26.0					26.0
	27.8					27.8
	1	0	33	66	100	1
	2	0	33	66	100	2
	3	0	33	66	100	3
	ID	1	1	1	1	ID
	[DEG]	0~84	30~84	54~84	64~84	[DEG]
		4	4	4	4	
		25t	25t	25t	25t	

■ジブ定格総荷重表

 FAJ	 8.2m		 6.6m	 360°	 JPN
---	--	--	--	--	---

 m		9.35	9.35	9.35	9.35	23.45	23.45	23.45	23.45	30.5	30.5	30.5	30.5	m
 °		5	25	45	60	5	25	45	60	5	25	45	60	°
 m	2.0	3.30												2.0
	3.0	3.30												3.0
	3.5	3.30												3.5
	4.0	3.30				3.30								4.0
	4.5	3.30	2.30			3.30								4.5
	5.0	3.30	2.30			3.30								5.0
	5.5	3.30	2.30			3.30				3.30				5.5
	6.0	3.30	2.30			3.30				3.30				6.0
	6.5	3.30	2.30	1.70		3.30				3.30				6.5
	7.0	3.30	2.30	1.70		3.30	2.30			3.30				7.0
	8.0	3.30	2.30	1.70	1.10	3.30	2.30			3.30				8.0
	9.0	3.15	2.30	1.70	1.10	3.30	2.30	1.70		3.30	2.30			9.0
	10.0	2.90	2.30	1.70	1.10	3.30	2.30	1.70	1.10	3.30	2.30			10.0
	11.0	2.65	2.30	1.70	1.10	3.30	2.30	1.70	1.10	3.30	2.30	1.70	1.10	11.0
	12.0	2.50	2.20	1.70		3.30	2.30	1.70	1.10	3.30	2.30	1.70	1.10	12.0
	13.0	2.30	2.10	1.70		3.30	2.30	1.70	1.10	3.30	2.30	1.70	1.10	13.0
	14.0	2.20	2.05			3.20	2.30	1.70	1.10	3.30	2.30	1.70	1.10	14.0
	16.0					2.85	2.30	1.70	1.10	3.00	2.30	1.70	1.10	16.0
	18.0					2.55	2.20	1.70	1.10	2.55	2.15	1.65	1.10	18.0
	20.0					2.00	2.00	1.70		2.00	2.00	1.55	1.10	20.0
	22.0					1.55	1.70	1.55		1.55	1.70	1.50	1.10	22.0
	23.0					1.40	1.50	1.55		1.35	1.50	1.45	1.10	23.0
	24.0					1.20	1.30			1.20	1.30	1.40		24.0
	26.0					0.95	1.00			0.90	1.00	1.05		26.0
	27.0					0.82	0.87			0.76	0.88	0.94		27.0
	28.0					0.71				0.63	0.74	0.78		28.0
	30.0									0.41	0.49			30.0
	32.0													32.0
	33.0													33.0
	34.0													34.0
 %	1	0	0	0	0	66	66	66	66	100	100	100	100	1
	2	0	0	0	0	66	66	66	66	100	100	100	100	2
	3	0	0	0	0	66	66	66	66	100	100	100	100	3
	ID	1	1	1	1	1	1	1	1	1	1	1	1	ID
 [DEG]		22~84	27~84	40~84	58~84	17~84	26~84	45~84	60~84	37~84	40~84	47~84	58~84	[DEG]

 FAJ	 8.2m		 6.1m	 360°	 JPN
---	--	--	--	--	---

 m		9.35	9.35	9.35	9.35	23.45	23.45	23.45	23.45	30.5	30.5	30.5	30.5	m
 °		5	25	45	60	5	25	45	60	5	25	45	60	°
 m	2.0	3.30												2.0
	3.0	3.30												3.0
	3.5	3.30												3.5
	4.0	3.30				3.30								4.0
	4.5	3.30	2.30			3.30								4.5
	5.0	3.30	2.30			3.30								5.0
	5.5	3.30	2.30			3.30				3.30				5.5
	6.0	3.30	2.30			3.30				3.30				6.0
	6.5	3.30	2.30	1.70		3.30				3.30				6.5
	7.0	3.30	2.30	1.70		3.30	2.30			3.30				7.0
	8.0	3.30	2.30	1.70	1.10	3.30	2.30			3.30				8.0
	9.0	3.15	2.30	1.70	1.10	3.30	2.30	1.70		3.30	2.30			9.0
	10.0	2.90	2.30	1.70	1.10	3.30	2.30	1.70	1.10	3.30	2.30			10.0
	11.0	2.65	2.30	1.70	1.10	3.30	2.30	1.70	1.10	3.30	2.30	1.70	1.10	11.0
	12.0	2.50	2.20	1.70		3.30	2.30	1.70	1.10	3.30	2.30	1.70	1.10	12.0
	13.0	2.30	2.10	1.70		3.30	2.30	1.70	1.10	3.30	2.30	1.70	1.10	13.0
	14.0	2.20	2.05			3.20	2.30	1.70	1.10	3.30	2.30	1.70	1.10	14.0
	16.0					2.85	2.30	1.70	1.10	2.85	2.30	1.70	1.10	16.0
	18.0					2.20	2.20	1.70	1.10	2.20	2.15	1.65	1.10	18.0
	20.0					1.70	1.85	1.70		1.70	1.90	1.55	1.10	20.0
	22.0					1.30	1.45	1.50		1.30	1.45	1.50	1.10	22.0
	23.0					1.15	1.25	1.30		1.10	1.25	1.35	1.10	23.0
	24.0					1.00	1.10			0.97	1.10	1.20		24.0
	26.0					0.75	0.81			0.69	0.82	0.88		26.0
	27.0					0.63	0.68			0.56	0.68	0.73		27.0
	28.0					0.53				0.44	0.55	0.59		28.0
	30.0										0.32			30.0
	32.0													32.0
	33.0													33.0
	34.0													34.0
 %	1	0	0	0	0	66	66	66	66	100	100	100	100	1
	2	0	0	0	0	66	66	66	66	100	100	100	100	2
	3	0	0	0	0	66	66	66	66	100	100	100	100	3
	ID	1	1	1	1	1	1	1	1	1	1	1	1	ID
 [DEG]		22~84	27~84	40~84	58~84	17~84	26~84	45~84	60~84	42~84	40~84	47~84	58~84	[DEG]

 FAJ	 8.2m		 5.0m	 360°	 JPN
---	--	--	--	--	---

 m	9.35	9.35	9.35	9.35	23.45	23.45	23.45	23.45	30.5	30.5	30.5	30.5	m
 °	5	25	45	60	5	25	45	60	5	25	45	60	°
 2.0	3.30												2.0
 3.0	3.30												3.0
 3.5	3.30												3.5
 4.0	3.30				3.30								4.0
 4.5	3.30	2.30			3.30								4.5
 5.0	3.30	2.30			3.30								5.0
 5.5	3.30	2.30			3.30				3.30				5.5
 6.0	3.30	2.30			3.30				3.30				6.0
 6.5	3.30	2.30	1.70		3.30				3.30				6.5
 7.0	3.30	2.30	1.70		3.30	2.30			3.30				7.0
 8.0	3.30	2.30	1.70	1.10	3.30	2.30			3.30				8.0
 9.0	3.15	2.30	1.70	1.10	3.30	2.30	1.70		3.30	2.30			9.0
 10.0	2.90	2.30	1.70	1.10	3.30	2.30	1.70	1.10	3.30	2.30			10.0
 11.0	2.65	2.30	1.70	1.10	3.30	2.30	1.70	1.10	3.30	2.30	1.70	1.10	11.0
 12.0	2.50	2.20	1.70		3.30	2.30	1.70	1.10	3.30	2.30	1.70	1.10	12.0
 13.0	2.30	2.10	1.70		3.10	2.30	1.70	1.10	3.10	2.30	1.70	1.10	13.0
 14.0	2.20	2.05			2.65	2.30	1.70	1.10	2.65	2.30	1.70	1.10	14.0
 16.0					1.95	2.20	1.70	1.10	1.95	2.20	1.70	1.10	16.0
 18.0					1.45	1.65	1.70	1.10	1.40	1.65	1.65	1.10	18.0
 20.0					1.05	1.20	1.30		1.00	1.20	1.35	1.10	20.0
 22.0					0.75	0.87	0.93		0.72	0.88	0.99	1.00	22.0
 23.0					0.61	0.72	0.77		0.57	0.73	0.82	0.84	23.0
 24.0					0.49	0.58			0.43	0.59	0.68		24.0
 26.0						0.34				0.32	0.39		26.0
 27.0													27.0
 28.0													28.0
 30.0													30.0
 32.0													32.0
 33.0													33.0
 34.0													34.0
 1	0	0	0	0	66	66	66	66	100	100	100	100	1
 2	0	0	0	0	66	66	66	66	100	100	100	100	2
 3	0	0	0	0	66	66	66	66	100	100	100	100	3
 ID	1	1	1	1	1	1	1	1	1	1	1	1	ID
 [DEG]	22~84	27~84	40~84	58~84	36~84	32~84	45~84	60~84	51~84	50~84	52~84	58~84	[DEG]

 FAJ	 8.2m		 3.6m	 360°	 JPN
---	--	--	--	--	---

 m	9.35	9.35	9.35	9.35	23.45	23.45	23.45	23.45	30.5	30.5	30.5	30.5	m
 °	5	25	45	60	5	25	45	60	5	25	45	60	°
 2.0	3.30												2.0
 3.0	3.30												3.0
 3.5	3.30												3.5
 4.0	3.30				3.30								4.0
 4.5	3.30	2.30			3.30								4.5
 5.0	3.30	2.30			3.30								5.0
 5.5	3.30	2.30			3.30				3.30				5.5
 6.0	3.30	2.30			3.30				3.30				6.0
 6.5	3.30	2.30	1.70		3.30				3.30				6.5
 7.0	3.30	2.30	1.70		3.30	2.30			3.30				7.0
 8.0	3.30	2.30	1.70	1.10	3.30	2.30			3.30				8.0
 9.0	3.15	2.30	1.70	1.10	3.30	2.30	1.70		3.30	2.30			9.0
 10.0	2.90	2.30	1.70	1.10	3.05	2.30	1.70	1.10	2.85	2.30			10.0
 11.0	2.65	2.30	1.70	1.10	2.50	2.30	1.70	1.10	2.35	2.30	1.70	1.10	11.0
 12.0	2.40	2.20	1.70		2.05	2.30	1.70	1.10	1.95	2.30	1.70	1.10	12.0
 13.0	2.05	2.10	1.70		1.70	2.00	1.70	1.10	1.60	2.00	1.70	1.10	13.0
 14.0	1.75	1.85			1.40	1.70	1.70	1.10	1.30	1.65	1.70	1.10	14.0
 16.0					0.92	1.15	1.30	1.10	0.84	1.10	1.35	1.10	16.0
 18.0					0.56	0.75	0.88	0.92		0.72	0.91	0.99	18.0
 20.0						0.43	0.52				0.53	0.59	20.0
 22.0													22.0
 23.0													23.0
 24.0													24.0
 26.0													26.0
 27.0													27.0
 28.0													28.0
30.0													30.0
32.0													32.0
33.0													33.0
34.0													34.0
1	0	0	0	0	66	66	66	66	100	100	100	100	1
2	0	0	0	0	66	66	66	66	100	100	100	100	2
3	0	0	0	0	66	66	66	66	100	100	100	100	3
ID	1	1	1	1	1	1	1	1	1	1	1	1	ID
[DEG]	22~84	27~84	40~84	58~84	53~84	52~84	55~84	61~84	65~84	65~84	64~84	65~84	[DEG]

 FAJ	 13.0m		 6.6m	 360°	 JPN
---	---	--	--	--	---

 m		9.35	9.35	9.35	9.35	23.45	23.45	23.45	23.45	30.5	30.5	30.5	30.5	m
 °		5	25	45	60	5	25	45	60	5	25	45	60	°
 m	2.0													2.0
	3.0	2.20												3.0
	3.5	2.20												3.5
	4.0	2.20												4.0
	4.5	2.20												4.5
	5.0	2.20												5.0
	5.5	2.20				2.20								5.5
	6.0	2.20				2.20								6.0
	6.5	2.10				2.20				2.20				6.5
	7.0	2.00	1.30			2.20				2.20				7.0
	8.0	1.80	1.30			2.20				2.20				8.0
	9.0	1.65	1.30			2.20				2.20				9.0
	10.0	1.55	1.30			2.10	1.30			2.20				10.0
	11.0	1.40	1.20	0.85		2.00	1.30			2.20	1.30			11.0
	12.0	1.30	1.15	0.85	0.65	1.85	1.30			2.15	1.30			12.0
	13.0	1.25	1.10	0.85	0.65	1.75	1.30	0.85		2.05	1.30			13.0
	14.0	1.15	1.05	0.85	0.65	1.70	1.25	0.85		1.95	1.30			14.0
	16.0	1.05	0.98	0.85	0.65	1.50	1.20	0.85	0.65	1.75	1.25	0.85	0.65	16.0
	18.0	0.97	0.93			1.40	1.10	0.85	0.65	1.60	1.20	0.85	0.65	18.0
	20.0					1.30	1.05	0.85	0.64	1.50	1.15	0.85	0.64	20.0
	22.0					1.20	1.00	0.85	0.62	1.40	1.10	0.85	0.62	22.0
	23.0					1.15	1.00	0.85	0.61	1.35	1.05	0.85	0.61	23.0
	24.0					1.10	0.99	0.85		1.30	1.05	0.85	0.60	24.0
	26.0					1.05	0.95	0.85		1.15	1.00	0.83	0.60	26.0
	27.0					1.00	0.92	0.85		1.00	0.97	0.82	0.60	27.0
	28.0					0.95	0.90	0.85		0.91	0.94	0.81	0.60	28.0
	30.0					0.78	0.84			0.69	0.85	0.80		30.0
	32.0					0.60	0.65			0.49	0.63	0.65		32.0
	33.0					0.52				0.40	0.53	0.58		33.0
	34.0									0.32	0.43	0.47		34.0
 %	1	0	0	0	0	66	66	66	66	100	100	100	100	1
	2	0	0	0	0	66	66	66	66	100	100	100	100	2
	3	0	0	0	0	66	66	66	66	100	100	100	100	3
	ID	1	1	1	1	1	1	1	1	1	1	1	1	ID
 [DEG]		27~84	36~84	56~84	57~84	17~84	28~84	44~84	61~84	39~84	45~84	45~84	60~84	[DEG]

 FAJ	 13.0m		 6.1m	 360°	 JPN
---	---	--	--	--	---

 m		9.35	9.35	9.35	9.35	23.45	23.45	23.45	23.45	30.5	30.5	30.5	30.5	m
 °		5	25	45	60	5	25	45	60	5	25	45	60	°
 m	2.0													2.0
	3.0	2.20												3.0
	3.5	2.20												3.5
	4.0	2.20												4.0
	4.5	2.20												4.5
	5.0	2.20												5.0
	5.5	2.20				2.20								5.5
	6.0	2.20				2.20								6.0
	6.5	2.10				2.20				2.20				6.5
	7.0	2.00	1.30			2.20				2.20				7.0
	8.0	1.80	1.30			2.20				2.20				8.0
	9.0	1.65	1.30			2.20				2.20				9.0
	10.0	1.55	1.30			2.10	1.30			2.20				10.0
	11.0	1.40	1.20	0.85		2.00	1.30			2.20	1.30			11.0
	12.0	1.30	1.15	0.85	0.65	1.85	1.30			2.15	1.30			12.0
	13.0	1.25	1.10	0.85	0.65	1.75	1.30	0.85		2.05	1.30			13.0
	14.0	1.15	1.05	0.85	0.65	1.70	1.25	0.85		1.95	1.30			14.0
	16.0	1.05	0.98	0.85	0.65	1.50	1.20	0.85	0.65	1.75	1.25	0.85	0.65	16.0
	18.0	0.97	0.93			1.40	1.10	0.85	0.65	1.60	1.20	0.85	0.65	18.0
	20.0					1.30	1.05	0.85	0.64	1.50	1.15	0.85	0.64	20.0
	22.0					1.20	1.00	0.85	0.62	1.40	1.10	0.85	0.62	22.0
	23.0					1.15	1.00	0.85	0.61	1.35	1.05	0.85	0.61	23.0
	24.0					1.10	0.99	0.85		1.20	1.05	0.85	0.60	24.0
	26.0					1.00	0.95	0.85		0.96	1.00	0.83	0.60	26.0
	27.0					0.92	0.92	0.85		0.84	0.97	0.82	0.60	27.0
	28.0					0.81	0.90	0.85		0.72	0.91	0.81	0.60	28.0
	30.0					0.62	0.70			0.51	0.68	0.77		30.0
	32.0					0.45	0.50			0.33	0.47	0.53		32.0
	33.0					0.38					0.37	0.42		33.0
	34.0											0.32		34.0
 %	1	0	0	0	0	66	66	66	66	100	100	100	100	1
	2	0	0	0	0	66	66	66	66	100	100	100	100	2
	3	0	0	0	0	66	66	66	66	100	100	100	100	3
	ID	1	1	1	1	1	1	1	1	1	1	1	1	ID
 [DEG]		27~84	36~84	56~84	57~84	17~84	28~84	44~84	61~84	43~84	47~84	45~84	60~84	[DEG]

 FAJ	 13.0m		 5.0m	 360°	 JPN
---	---	--	--	--	---

 m		9.35	9.35	9.35	9.35	23.45	23.45	23.45	23.45	30.5	30.5	30.5	30.5	m
 °		5	25	45	60	5	25	45	60	5	25	45	60	°
	2.0													2.0
	3.0	2.20												3.0
	3.5	2.20												3.5
	4.0	2.20												4.0
	4.5	2.20												4.5
	5.0	2.20												5.0
	5.5	2.20				2.20								5.5
	6.0	2.20				2.20								6.0
	6.5	2.10				2.20				2.20				6.5
	7.0	2.00	1.30			2.20				2.20				7.0
	8.0	1.80	1.30			2.20				2.20				8.0
	9.0	1.65	1.30			2.20				2.20				9.0
	10.0	1.55	1.30			2.10	1.30			2.20				10.0
	11.0	1.40	1.20	0.85		2.00	1.30			2.20	1.30			11.0
	12.0	1.30	1.15	0.85	0.65	1.85	1.30			2.15	1.30			12.0
	13.0	1.25	1.10	0.85	0.65	1.75	1.30	0.85		2.05	1.30			13.0
	14.0	1.15	1.05	0.85	0.65	1.70	1.25	0.85		1.95	1.30			14.0
	16.0	1.05	0.98	0.85	0.65	1.50	1.20	0.85	0.65	1.75	1.25	0.85	0.65	16.0
	18.0	0.97	0.93			1.40	1.10	0.85	0.65	1.60	1.20	0.85	0.65	18.0
	20.0					1.30	1.05	0.85	0.64	1.30	1.15	0.85	0.64	20.0
	22.0					1.00	1.00	0.85	0.62	0.97	1.10	0.85	0.62	22.0
	23.0					0.90	1.00	0.85	0.61	0.83	1.05	0.85	0.61	23.0
	24.0					0.78	0.96	0.85		0.71	0.94	0.85	0.60	24.0
	26.0					0.56	0.71	0.80		0.47	0.69	0.83	0.60	26.0
	27.0					0.46	0.60	0.67		0.37	0.57	0.70	0.60	27.0
	28.0					0.37	0.49	0.55			0.46	0.58	0.60	28.0
	30.0						0.30					0.35		30.0
	32.0													32.0
	33.0													33.0
	34.0													34.0
	1	0	0	0	0	66	66	66	66	100	100	100	100	1
	2	0	0	0	0	66	66	66	66	100	100	100	100	2
	3	0	0	0	0	66	66	66	66	100	100	100	100	3
	ID	1	1	1	1	1	1	1	1	1	1	1	1	ID
	[DEG]	27~84	36~84	56~84	57~84	38~84	37~84	45~84	61~84	53~84	56~84	54~84	60~84	[DEG]

 FAJ	 13.0m		 3.6m	 360°	 JPN
---	---	--	--	--	---

 m		9.35	9.35	9.35	9.35	23.45	23.45	23.45	23.45	30.5	30.5	30.5	30.5	m
 °		5	25	45	60	5	25	45	60	5	25	45	60	°
	2.0													2.0
	3.0	2.20												3.0
	3.5	2.20												3.5
	4.0	2.20												4.0
	4.5	2.20												4.5
	5.0	2.20												5.0
	5.5	2.20				2.20								5.5
	6.0	2.20				2.20								6.0
	6.5	2.10				2.20				2.20				6.5
	7.0	2.00	1.30			2.20				2.20				7.0
	8.0	1.80	1.30			2.20				2.20				8.0
	9.0	1.65	1.30			2.20				2.20				9.0
	10.0	1.55	1.30			2.10	1.30			2.20				10.0
	11.0	1.40	1.20	0.85		2.00	1.30			2.20	1.30			11.0
	12.0	1.30	1.15	0.85	0.65	1.85	1.30			2.15	1.30			12.0
	13.0	1.25	1.10	0.85	0.65	1.75	1.30	0.85		1.90	1.30			13.0
	14.0	1.15	1.05	0.85	0.65	1.70	1.25	0.85		1.60	1.30			14.0
	16.0	1.05	0.98	0.85	0.65	1.20	1.20	0.85	0.65	1.10	1.25	0.85	0.65	16.0
	18.0	0.97	0.93			0.86	1.10	0.85	0.65	0.75	1.15	0.85	0.65	18.0
	20.0					0.57	0.83	0.85	0.64		0.79	0.85	0.64	20.0
	22.0					0.33	0.55	0.72	0.62		0.49	0.73	0.62	22.0
	23.0						0.43	0.58	0.61			0.58	0.61	23.0
	24.0						0.32	0.45					0.52	24.0
	26.0													26.0
	27.0													27.0
	28.0													28.0
	30.0													30.0
	32.0													32.0
	33.0													33.0
	34.0													34.0
	1	0	0	0	0	66	66	66	66	100	100	100	100	1
	2	0	0	0	0	66	66	66	66	100	100	100	100	2
	3	0	0	0	0	66	66	66	66	100	100	100	100	3
	ID	1	1	1	1	1	1	1	1	1	1	1	1	ID
	[DEG]	27~84	36~84	56~84	57~84	52~84	54~84	57~84	61~84	66~84	66~84	68~84	68~84	[DEG]