

ブーム	ジブ	アウトリガ	作業範囲
		 前方	

 [m]		10.1	17.6		25.1	25.0	32.5		36.5		40.0
 [m]	1.8	60.00	30.00	14.00	15.00	12.50					
	2.1	57.00	30.00	14.00	15.00	12.50					
	2.5	53.50	30.00	14.00	15.00	12.50					
	3.0	50.00	30.00	14.00	15.00	12.50					
	3.2	45.00	30.00	14.00	15.00	12.50	12.50	7.50			
	3.5	41.00	30.00	14.00	15.00	12.50	12.50	7.50	9.00	7.50	
	4.0	37.00	30.00	14.00	15.00	12.50	12.50	7.50	9.00	7.50	
	4.5	33.50	30.00	14.00	15.00	12.50	12.50	7.50	9.00	7.50	7.50
	5.0	30.20	28.00	14.00	15.00	12.50	12.50	7.50	9.00	7.50	7.50
	5.5	27.50	26.10	14.00	15.00	12.50	12.50	7.50	9.00	7.50	7.50
	6.0	25.00	24.40	14.00	15.00	12.50	12.50	7.50	9.00	7.50	7.50
	6.5	22.70	22.40	14.00	15.00	12.50	12.50	7.50	9.00	7.50	7.50
	7.0	20.70	20.60	14.00	15.00	11.95	12.50	7.50	9.00	7.50	7.50
	7.5		18.90	14.00	15.00	11.35	12.50	7.50	9.00	7.50	7.50
	8.0		17.50	14.00	15.00	10.70	12.50	7.50	9.00	7.50	7.50
	8.5		16.20	14.00	15.00	10.15	12.50	7.50	9.00	7.50	7.50
	9.0		15.00	13.80	14.50	9.65	12.50	7.50	9.00	7.50	7.50
	10.0		13.00	12.80	13.20	8.80	11.65	6.90	9.00	7.50	7.50
	11.0		11.10	11.80	11.60	8.05	10.70	6.25	9.00	7.20	7.50
	12.0		9.50	10.90	10.40	7.40	9.85	5.70	8.55	6.60	7.40
	13.0		8.20	10.00	9.20	6.85	9.00	5.25	7.90	6.05	6.85
	14.0		7.00	9.35	8.00	6.35	8.30	4.85	7.35	5.60	6.35
	15.0				7.00	5.90	7.60	4.45	6.85	5.20	5.90
	16.0				6.20	5.50	7.00	4.15	6.40	4.80	5.50
	17.0				5.60	5.20	6.40	3.85	6.00	4.50	5.15
	18.0				5.00	4.85	5.80	3.60	5.65	4.20	4.80
	19.0				4.40	4.60	5.20	3.35	5.30	3.90	4.50
	20.0				4.00	4.35	4.60	3.15	5.00	3.70	4.25
	21.0				3.60	4.10	4.20	2.95	4.65	3.45	4.00
	22.0				3.20	3.90	3.80	2.75	4.15	3.25	3.80
	24.0						3.00	2.45	3.35	2.90	3.40
	26.0						2.30	2.20	2.70	2.60	2.80
	28.0						1.80	1.95	2.15	2.35	2.30
	30.0								1.70	2.10	1.80
	32.0								1.35	1.95	1.45
	33.0								1.20	1.85	1.25
	34.0										1.10
	36.0										0.85
	37.0										0.75
	ブーム 2(%)	0	100	0	100	0	100	0	100	50	100
	ブーム 3(%)	0	0	33	33	66	66	100	83	100	100
	ブーム 4(%)	0	0	33	33	66	66	100	83	100	100
	ブーム 5(%)	0	0	33	33	66	66	100	83	100	100
	MODE	A,B	A	B	A	B	A	B	A	B	A,B
 危険 角度	[°]	—	—	—	—	—	—	—	—	—	—
 標準 フック	[ton]	60	34								
 フック 質量	[kg]	500	310								
 巻掛 本数	[本]	13	7	4	6	4	4	4	4	4	4

(単位 : ton)

ブーム 	ジブ	アウトリガ  7.6m	作業範囲 
--	----	--	---

 [m]		10.1	17.6		25.1	25.0	32.5		36.5		40.0
 [m]	1.8	60.00	30.00	14.00	15.00	12.50					
	2.1	57.00	30.00	14.00	15.00	12.50					
	2.5	53.50	30.00	14.00	15.00	12.50					
	3.0	50.00	30.00	14.00	15.00	12.50					
	3.2	45.00	30.00	14.00	15.00	12.50	12.50	7.50			
	3.5	41.00	30.00	14.00	15.00	12.50	12.50	7.50	9.00	7.50	
	4.0	37.00	30.00	14.00	15.00	12.50	12.50	7.50	9.00	7.50	
	4.5	33.50	30.00	14.00	15.00	12.50	12.50	7.50	9.00	7.50	7.50
	5.0	30.20	28.00	14.00	15.00	12.50	12.50	7.50	9.00	7.50	7.50
	5.5	27.50	26.10	14.00	15.00	12.50	12.50	7.50	9.00	7.50	7.50
	6.0	25.00	24.40	14.00	15.00	12.50	12.50	7.50	9.00	7.50	7.50
	6.5	22.70	22.40	14.00	15.00	12.50	12.50	7.50	9.00	7.50	7.50
	7.0	20.70	20.60	14.00	15.00	11.95	12.50	7.50	9.00	7.50	7.50
	7.5		18.90	14.00	15.00	11.35	12.50	7.50	9.00	7.50	7.50
	8.0		17.50	14.00	15.00	10.70	12.50	7.50	9.00	7.50	7.50
	8.5		16.20	14.00	15.00	10.15	12.50	7.50	9.00	7.50	7.50
	9.0		15.00	13.80	14.50	9.65	12.50	7.50	9.00	7.50	7.50
	10.0		12.30	12.80	13.20	8.80	11.65	6.90	9.00	7.50	7.50
	11.0		10.05	11.80	11.20	8.05	10.70	6.25	9.00	7.20	7.50
	12.0		8.35	10.25	9.40	7.40	9.85	5.70	8.55	6.60	7.40
	13.0		7.00	8.85	8.00	6.85	8.60	5.25	7.90	6.05	6.85
	14.0		5.90	7.70	6.90	6.35	7.45	4.85	7.35	5.60	6.35
	15.0				6.00	5.90	6.55	4.45	6.70	5.20	5.90
	16.0				5.25	5.50	5.75	4.15	5.90	4.80	5.50
	17.0				4.60	5.20	5.10	3.85	5.25	4.50	5.15
	18.0				4.00	4.85	4.50	3.60	4.65	4.20	4.80
	19.0				3.50	4.60	4.00	3.35	4.15	3.90	4.30
	20.0				3.05	4.25	3.55	3.15	3.75	3.70	3.90
	21.0				2.65	3.85	3.15	2.95	3.30	3.45	3.45
	22.0				2.30	3.50	2.80	2.75	2.95	3.25	3.10
	24.0						2.15	2.45	2.35	2.70	2.45
	26.0						1.65	2.20	1.80	2.20	1.95
	28.0						1.15	1.95	1.40	1.75	1.50
	30.0								1.00	1.40	1.10
32.0								0.70	1.10	0.80	
33.0								0.55	1.00	0.65	
34.0										0.50	
	ブーム 2(%)	0	100	0	100	0	100	0	100	50	100
	ブーム 3(%)	0	0	33	33	66	66	100	83	100	100
	ブーム 4(%)	0	0	33	33	66	66	100	83	100	100
	ブーム 5(%)	0	0	33	33	66	66	100	83	100	100
	MODE	A,B	A	B	A	B	A	B	A	B	A,B
 危険 角度	[°]	—	—	—	—	—	—	—	—	—	24
 標準 フック	[ton]	60	34								
 フック 質量	[kg]	500	310								
 巻掛 本数	[本]	13	7	4	6	4	4	4	4	4	4

(単位 : ton)

ブーム 	ジブ	アウトリガ  7.2m	作業範囲 
--	----	--	---

 [m]		10.1	17.6		25.1	25.0	32.5		36.5		40.0
 [m]	1.8	60.00	30.00	14.00	15.00	12.50					
	2.1	57.00	30.00	14.00	15.00	12.50					
	2.5	53.50	30.00	14.00	15.00	12.50					
	3.0	50.00	30.00	14.00	15.00	12.50					
	3.2	45.00	30.00	14.00	15.00	12.50	12.50	7.50			
	3.5	41.00	30.00	14.00	15.00	12.50	12.50	7.50	9.00	7.50	
	4.0	37.00	30.00	14.00	15.00	12.50	12.50	7.50	9.00	7.50	
	4.5	33.50	30.00	14.00	15.00	12.50	12.50	7.50	9.00	7.50	7.50
	5.0	30.20	28.00	14.00	15.00	12.50	12.50	7.50	9.00	7.50	7.50
	5.5	27.50	26.10	14.00	15.00	12.50	12.50	7.50	9.00	7.50	7.50
	6.0	25.00	24.40	14.00	15.00	12.50	12.50	7.50	9.00	7.50	7.50
	6.5	22.70	22.40	14.00	15.00	12.50	12.50	7.50	9.00	7.50	7.50
	7.0	20.70	20.60	14.00	15.00	11.95	12.50	7.50	9.00	7.50	7.50
	7.5		18.90	14.00	15.00	11.35	12.50	7.50	9.00	7.50	7.50
	8.0		17.50	14.00	15.00	10.70	12.50	7.50	9.00	7.50	7.50
	8.5		15.55	14.00	15.00	10.15	12.50	7.50	9.00	7.50	7.50
	9.0		13.75	13.80	14.50	9.65	12.50	7.50	9.00	7.50	7.50
	10.0		11.00	12.80	12.20	8.80	11.65	6.90	9.00	7.50	7.50
	11.0		9.00	10.95	10.10	8.05	10.70	6.25	9.00	7.20	7.50
	12.0		7.45	9.30	8.50	7.40	9.10	5.70	8.55	6.60	7.40
	13.0		6.25	8.05	7.25	6.85	7.80	5.25	7.90	6.05	6.85
	14.0		5.25	7.00	6.25	6.35	6.80	4.85	6.95	5.60	6.35
	15.0				5.40	5.90	5.90	4.45	6.10	5.20	5.90
	16.0				4.70	5.50	5.20	4.15	5.35	4.80	5.50
	17.0				4.05	5.20	4.60	3.85	4.75	4.50	4.85
	18.0				3.50	4.80	4.05	3.60	4.20	4.20	4.35
	19.0				3.00	4.30	3.55	3.35	3.75	3.90	3.85
	20.0				2.55	3.85	3.10	3.15	3.30	3.70	3.45
	21.0				2.15	3.50	2.70	2.95	2.90	3.35	3.05
	22.0				1.80	3.15	2.35	2.75	2.55	3.00	2.70
	24.0						1.75	2.45	1.90	2.40	2.05
	26.0						1.25	2.20	1.40	1.90	1.55
	28.0						0.80	1.85	1.00	1.50	1.10
	30.0								0.65	1.20	0.75
	32.0									0.90	
	33.0									0.80	
	ブーム 2(%)	0	100	0	100	0	100	0	100	50	100
	ブーム 3(%)	0	0	33	33	66	66	100	83	100	100
	ブーム 4(%)	0	0	33	33	66	66	100	83	100	100
	ブーム 5(%)	0	0	33	33	66	66	100	83	100	100
	MODE	A,B	A	B	A	B	A	B	A	B	A,B
	危険角度 [°]	—	—	—	—	—	—	—	25	—	35
	標準フック [ton]	60	34								
	フック質量 [kg]	500	310								
	巻掛本数 [本]	13	7	4	6	4	4	4	4	4	4

(単位 : ton)