

定格総荷重表

■主ブーム

(単位: t)

作業半径 (m)	主ブーム長さ (m)																		
	18.30	21.35	24.40	27.45	30.50	33.50	36.55	39.60	42.65	45.70	48.75	51.80	54.85	57.90	60.95	64.00	67.05	70.10	73.15
5.0	100.0																		
5.5	100.0	98.1																	
6.0	94.0	93.7	86.9	77.0/6.6															
7.0	81.1	80.8	80.6	76.0	66.0/7.1	62.2/7.6													
8.0	70.7	70.6	70.5	70.5	66.0	61.3	55.0/8.2	50.7/8.7											
9.0	59.0	58.9	58.8	58.8	58.7	58.6	54.9	50.3	44.0/9.2	41.9/9.8									
10.0	50.6	50.5	50.4	50.3	50.2	50.1	50.1	49.4	44.0	41.7	33.0/10.3	33.0/10.8	31.4/11.3	27.9/11.9					
12.0	39.1	39.0	38.9	38.8	38.7	38.5	38.5	38.3	38.3	38.1	33.0	33.0	30.9	27.8	22.0/12.5	22.0/13.0	21.2/13.5		
14.0	31.8	31.6	31.4	31.4	31.2	31.1	31.0	30.8	30.8	30.6	30.6	30.4	29.9	27.4	22.0	22.0	21.0	19.3/14.1	17.4/14.8
16.0	26.6	26.4	26.2	26.2	26.0	25.9	25.8	25.6	25.5	25.4	25.3	25.2	25.0	24.8	22.0	22.0	20.2	18.1	16.1
18.0	24.0/17.3	22.6	22.4	22.3	22.2	22.0	21.9	21.7	21.7	21.5	21.4	21.3	21.1	20.9	20.9	20.8	18.4	16.4	14.5
20.0		19.7	19.5	19.4	19.2	19.1	19.0	18.8	18.7	18.5	18.4	18.3	18.1	17.9	17.9	17.8	16.8	14.9	13.1
22.0			17.2	17.1	16.9	16.7	16.6	16.4	16.3	16.2	16.1	15.9	15.8	15.6	15.5	15.4	15.2	13.7	12.0
24.0			16.6/22.6	15.2	15.0	14.8	14.7	14.5	14.4	14.3	14.2	14.0	13.8	13.6	13.6	13.4	13.2	12.6	10.9
26.0				14.2/25.3	13.4	13.3	13.2	12.9	12.8	12.7	12.6	12.4	12.2	12.0	12.0	11.8	11.6	11.5	10.0
28.0					12.2/27.9	12.0	11.8	11.6	11.5	11.3	11.2	11.1	10.9	10.6	10.6	10.5	10.3	10.1	9.2
30.0						10.9	10.7	10.5	10.4	10.2	10.1	9.9	9.8	9.5	9.5	9.3	9.1	9.0	8.5
32.0						10.6/30.5	9.8	9.5	9.4	9.2	9.1	8.9	8.8	8.6	8.5	8.3	8.1	8.0	7.8
34.0							9.3/33.2	8.7	8.6	8.4	8.3	8.1	7.9	7.7	7.6	7.5	7.3	7.1	6.9
36.0								8.0/35.8	7.8	7.7	7.5	7.3	7.2	6.9	6.9	6.7	6.5	6.3	6.2
38.0									7.2	7.0	6.8	6.7	6.5	6.3	6.2	6.0	5.8	5.6	5.4
40.0									7.0/38.5	6.4	6.3	6.1	5.9	5.7	5.6	5.4	5.2	4.9	4.7
42.0										6.1/41.1	5.7	5.6	5.4	5.1	5.0	4.8	4.5	4.3	4.1
44.0											5.3/43.7	5.1	4.9	4.6	4.5	4.3	4.0	3.8	3.6
46.0												4.7	4.4	4.1	4.0	3.8	3.5	3.3	3.1
48.0												4.6/46.4	4.0	3.7	3.5	3.3	3.0	2.8	2.6
50.0													3.8/49.0	3.3	3.1	2.9	2.6	2.4	2.2
52.0														3.0/51.7	2.8	2.5	2.3		
54.0															2.4	2.2			
ロープ掛数	10	9	8	7	6	6	5	5	4	4	3	3	3	3	2	2	2	2	2

■ショートジブ

(単位: t)

作業半径 (m)	主ブーム長さ (m)																		
	18.30	21.35	24.40	27.45	30.50	33.50	36.55	39.60	42.65	45.70	48.75	51.80	54.85	57.90	60.95	64.00	67.05	70.10	
5.8	11.0																		
6.0	11.0	11.0/6.3	11.0/6.9																
7.0	11.0	11.0	11.0	11.0/7.4	11.0/7.9														
8.0	11.0	11.0	11.0	11.0	11.0	11.0/8.5													
9.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0/9.5											
10.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0/10.1	11.0/10.6	11.0/11.1	11.0/11.6							
12.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0/12.2	11.0/12.7	11.0/13.2	11.0/13.8			
14.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0/14.3	11.0/14.8
16.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0
18.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0
20.0	11.0/18.6	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0
22.0		11.0/21.3	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0
24.0			11.0/23.9	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	10.9
26.0				11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	10.1
28.0				11.0/26.5	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	10.8	10.7	10.4	10.4	10.2	10.0	9.3
30.0					11.0/29.2	10.6	10.5	10.3	10.2	10.0	9.9	9.7	9.5	9.3	9.2	9.1	8.9	8.6	
32.0						9.8/31.8	9.6	9.3	9.2	9.0	8.9	8.7	8.5	8.3	8.2	8.1	7.9	7.7	
34.0							8.7	8.5	8.3	8.2	8.0	7.8	7.7	7.4	7.4	7.2	7.0	6.8	
36.0							8.5/34.5	7.7	7.6	7.4	7.3	7.1	6.9	6.7	6.6	6.4	6.2	6.0	
38.0								7.4/37.1	6.9	6.8	6.6	6.4	6.2	6.0	5.9	5.8	5.5	5.3	
40.0									6.5/39.7	6.2	6.0	5.8	5.6	5.4	5.3	5.1	4.8	4.6	
42.0										5.7	5.5	5.3	5.1	4.8	4.7	4.5	4.2	4.0	
44.0										5.6/42.4	5.0	4.8	4.6	4.3	4.2	3.9	3.6	3.4	
46.0											4.8/45.0	4.3	4.1	3.8	3.7	3.4	3.1	2.9	
48.0												4.0/47.7	3.6	3.3	3.2	3.0	2.7	2.4	
50.0													3.3	2.9	2.8	2.6	2.3		
52.0														3.2/50.3	2.6	2.4	2.2		
54.0															2.4/52.9	2.1			
ロープ掛数	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1

定格総荷重表

■ ショートジブ付き主ブーム

作業半径 (m)	主ブーム長さ (m)																	
	18.30	21.35	24.40	27.45	30.50	33.50	36.55	39.60	42.65	45.70	48.75	51.80	54.85	57.90	60.95	64.00	67.05	70.10
5.0	100.0																	
5.5	100.0	97.4																
6.0	93.2	92.9	86.1	76.3/6.6														
7.0	80.3	80.0	79.7	75.3	66.0/7.1	61.6/7.6												
8.0	70.0	69.9	69.8	69.7	66.0	60.7	55.0/8.2	50.4/8.7										
9.0	58.4	58.3	58.2	58.1	58.0	57.9	54.2	50.0	44.0/9.2	41.5/9.8								
10.0	49.9	49.8	49.7	49.6	49.5	49.4	49.4	48.6	44.0	41.3	33.0/10.3	33.0/10.8	30.8/11.3	27.2/11.9				
12.0	38.5	38.3	38.2	38.1	38.0	37.9	37.8	37.6	37.6	37.4	33.0	32.9	30.3	27.1	22.0/12.5	22.0/13.0	20.4/13.5	
14.0	31.1	30.9	30.8	30.7	30.5	30.4	30.3	30.1	30.1	29.9	29.8	29.7	29.1	26.6	22.0	22.0	20.2	18.5/14.1
16.0	26.0	25.8	25.6	25.5	25.3	25.2	25.1	24.9	24.8	24.7	24.6	24.4	24.2	24.0	22.0	21.3	19.4	17.2
18.0	23.4/17.3	22.0	21.8	21.7	21.5	21.3	21.3	21.0	21.0	20.8	20.7	20.5	20.4	20.2	20.1	19.9	17.5	15.5
20.0		19.1	18.9	18.7	18.6	18.4	18.3	18.1	18.0	17.8	17.7	17.5	17.4	17.2	17.1	17.0	15.9	14.0
22.0			16.6	16.4	16.2	16.0	16.0	15.7	15.6	15.5	15.3	15.2	15.0	14.8	14.8	14.6	14.4	12.8
24.0			16.0/22.6	14.6	14.3	14.2	14.1	13.8	13.7	13.5	13.4	13.3	13.1	12.9	12.8	12.6	12.4	11.7
26.0				13.5/25.3	12.8	12.6	12.5	12.2	12.1	12.0	11.8	11.7	11.5	11.3	11.2	11.0	10.8	10.7
28.0					11.6/27.9	11.3	11.2	10.9	10.8	10.6	10.5	10.3	10.2	9.9	9.9	9.7	9.5	9.3
30.0						10.2	10.1	9.8	9.7	9.5	9.4	9.2	9.0	8.8	8.7	8.5	8.3	8.2
32.0						10.0/30.5	9.1	8.8	8.7	8.5	8.4	8.2	8.0	7.8	7.7	7.6	7.3	7.2
34.0							8.6/33.2	8.0	7.9	7.7	7.5	7.4	7.2	6.9	6.9	6.7	6.5	6.3
36.0								7.4/35.8	7.2	7.0	6.8	6.6	6.4	6.2	6.1	5.9	5.6	5.4
38.0									6.5	6.3	6.1	6.0	5.8	5.5	5.4	5.1	4.9	4.6
40.0									6.4/38.5	5.7	5.6	5.4	5.1	4.8	4.7	4.5	4.2	4.0
42.0										5.5/41.1	5.0	4.8	4.5	4.2	4.1	3.9	3.6	3.3
44.0											4.6/43.7	4.3	4.0	3.7	3.6	3.3	3.0	2.8
46.0												3.8	3.5	3.2	3.1	2.8	2.5	
48.0												3.7/46.4	3.1	2.8	2.6	2.4		
50.0													2.9/49.0	2.4	2.2			
51.7														2.1				
ロープ掛数	10	9	8	7	6	6	5	5	4	4	3	3	3	3	2	2	2	2

定格総荷重表

■補助ジブ

(単位：t)

主フォーム長さ(m) 補助ジブ長さ(m) 作業半径 (m)	39.60						42.65						45.70					
	12.20		18.30		24.40		12.20		18.30		24.40		12.20		18.30		24.40	
	オフセット角度 (°)						オフセット角度 (°)						オフセット角度 (°)					
	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30
12.9	11.0						11.0/13.5											
14.0	11.0	8.0/15.9	10.0/15.5				11.0						11.0					
16.0	11.0	8.0	10.0		6.0/17.7		11.0	8.0/16.4	10.0				11.0	8.0/17.0	10.0/16.5			
18.0	11.0	8.0	10.0	6.0/19.7	6.0		11.0	8.0	10.0			6.0/18.2	11.0	8.0	10.0			6.0/18.7
20.0	11.0	8.0	10.0	6.0	6.0		11.0	8.0	10.0	6.0/20.3	6.0		11.0	8.0	10.0	6.0/20.8	6.0	
22.0	11.0	8.0	10.0	6.0	6.0	4.5/23.3	11.0	8.0	10.0	6.0	6.0	4.5/23.8	11.0	8.0	10.0	6.0	6.0	
24.0	11.0	8.0	10.0	6.0	6.0	4.5	11.0	8.0	10.0	6.0	6.0	4.5	11.0	8.0	10.0	6.0	6.0	4.5/24.4
26.0	11.0	8.0	10.0	6.0	6.0	4.5	11.0	8.0	10.0	6.0	6.0	4.5	11.0	8.0	10.0	6.0	6.0	4.5
28.0	11.0	8.0	10.0	6.0	6.0	4.5	11.0	8.0	9.9	6.0	6.0	4.5	11.0	8.0	9.7	6.0	6.0	4.5
30.0	10.9	8.0	10.0	6.0	6.0	4.5	10.7	8.0	9.7	6.0	6.0	4.5	10.6	8.0	9.3	6.0	6.0	4.5
32.0	9.9	8.0	9.7	6.0	6.0	4.5	9.7	8.0	9.4	6.0	6.0	4.5	9.5	8.0	8.9	6.0	6.0	4.5
34.0	9.0	7.8	9.2	6.0	6.0	4.5	8.8	8.0	8.9	6.0	6.0	4.5	8.7	8.0	8.4	6.0	6.0	4.5
36.0	8.2	7.6	8.4	6.0	6.0	4.5	8.0	7.8	8.3	6.0	6.0	4.5	7.9	8.0	7.9	6.0	6.0	4.5
38.0	7.5	7.4	7.8	6.0	6.0	4.5	7.3	7.5	7.6	6.0	6.0	4.5	7.2	7.4	7.4	6.0	6.0	4.5
40.0	6.9	7.0	7.1	5.9	5.9	4.5	6.7	6.9	7.0	5.7	6.0	4.5	6.6	6.8	6.8	5.5	6.0	4.5
42.0	6.3	6.5	6.6	5.4	5.7	4.5	6.2	6.3	6.4	5.4	5.9	4.5	6.0	6.2	6.3	5.4	6.0	4.5
44.0	5.8	5.9	6.1	5.2	5.6	4.5	5.7	5.8	5.9	5.3	5.7	4.5	5.5	5.7	5.8	5.4	5.8	4.5
46.0	5.4	5.5	5.6	5.1	5.5	4.5	5.2	5.3	5.4	5.2	5.6	4.4	5.1	5.2	5.3	5.3	5.5	4.2
48.0	5.0/47.7	5.0	5.2	5.0	5.3	4.2	4.8	4.9	5.0	5.1	5.2	4.0	4.7	4.8	4.9	5.1	5.0	4.1
50.0		4.9/48.3	4.8	4.9	5.0	4.0	4.4	4.5	4.6	4.8	4.8	4.0	4.3	4.4	4.5	4.7	4.7	4.0
52.0			4.4	4.5	4.6	3.9	4.4/50.3	4.3/51.0	4.3	4.4	4.4	3.9	3.9	3.9	4.1	4.3	4.3	4.0
54.0			4.2/53.6	4.2	4.3	3.8			4.0	4.1	4.1	3.9	3.7/52.9	3.6/53.6	3.8	3.9	4.0	3.9
56.0				4.1/54.4	4.0	3.7			3.6	3.7	3.8	3.8			3.4	3.6	3.6	3.9
58.0					3.7	3.6			3.6/56.2	3.5/57.1	3.5	3.7			3.1	3.2	3.3	3.5
ロープ掛数	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1

主フォーム長さ(m) 補助ジブ長さ(m) 作業半径 (m)	48.75						51.80						54.85					
	12.20		18.30		24.40		12.20		18.30		24.40		12.20		18.30		24.40	
	オフセット角度 (°)						オフセット角度 (°)						オフセット角度 (°)					
	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30
12.9																		
14.0	11.0/14.5						11.0/15.0						11.0/15.6					
16.0	11.0	8.0/17.5	10.0/17.0				11.0		10.0/17.6				11.0					
18.0	11.0	8.0	10.0		6.0/19.3		11.0	8.0	10.0			6.0/19.8	11.0	8.0/18.5	10.0/18.1			
20.0	11.0	8.0	10.0	6.0/21.3	6.0		11.0	8.0	10.0	6.0/21.9	6.0		11.0	8.0	10.0		6.0/20.3	
22.0	11.0	8.0	10.0	6.0	6.0		11.0	8.0	10.0	6.0	6.0		11.0	8.0	10.0	6.0/22.4	6.0	
24.0	11.0	8.0	10.0	6.0	6.0	4.5/24.9	11.0	8.0	10.0	6.0	6.0	4.5/25.4	11.0	8.0	10.0	6.0	6.0	4.5/25.9
26.0	11.0	8.0	10.0	6.0	6.0	4.5	11.0	8.0	10.0	6.0	6.0	4.5	11.0	8.0	10.0	6.0	6.0	4.5
28.0	11.0	8.0	9.6	6.0	6.0	4.5	11.0	8.0	9.4	6.0	6.0	4.5	11.0	8.0	9.2	6.0	6.0	4.5
30.0	10.4	8.0	9.2	6.0	6.0	4.5	10.2	8.0	8.9	6.0	6.0	4.5	10.1	8.0	8.7	6.0	6.0	4.5
32.0	9.3	8.0	8.7	6.0	6.0	4.5	9.2	8.0	8.4	6.0	6.0	4.5	9.0	8.0	8.3	6.0	6.0	4.5
34.0	8.4	8.0	8.2	6.0	6.0	4.5	8.3	8.0	7.9	6.0	6.0	4.5	8.2	8.0	7.8	6.0	6.0	4.5
36.0	7.7	7.9	7.7	6.0	6.0	4.5	7.5	7.8	7.5	6.0	6.0	4.5	7.4	7.7	7.3	6.0	6.0	4.5
38.0	7.0	7.2	7.2	5.9	6.0	4.5	6.8	7.1	7.0	5.9	6.0	4.5	6.7	6.9	6.8	6.0	6.0	4.5
40.0	6.4	6.6	6.6	5.7	6.0	4.5	6.2	6.4	6.5	5.8	6.0	4.5	6.1	6.3	6.3	5.8	6.0	4.5
42.0	5.8	6.0	6.1	5.5	6.0	4.5	5.6	5.9	5.9	5.6	6.0	4.5	5.5	5.7	5.8	5.7	6.0	4.5
44.0	5.3	5.5	5.5	5.4	5.7	4.5	5.1	5.3	5.4	5.5	5.6	4.5	5.0	5.2	5.2	5.6	5.4	4.5
46.0	4.8	5.0	5.1	5.2	5.3	4.3	4.7	4.8	4.9	5.2	5.1	4.3	4.5	4.7	4.8	5.1	5.0	4.4
48.0	4.4	4.6	4.7	4.9	4.8	4.1	4.2	4.4	4.5	4.8	4.7	4.2	4.0	4.2	4.3	4.6	4.5	4.3
50.0	4.0	4.1	4.3	4.5	4.4	4.0	3.8	3.9	4.1	4.3	4.3	4.1	3.6	3.8	3.9	4.2	4.1	4.2
52.0	3.6	3.7	3.9	4.1	4.1	3.9	3.4	3.5	3.7	3.9	3.9	4.0	3.2	3.3	3.5	3.8	3.7	4.1
54.0	3.2	3.3	3.5	3.7	3.7	3.9	3.0	3.1	3.3	3.5	3.5	3.8	2.8	3.0	3.1	3.4	3.3	3.7
56.0	2.9/55.6	2.9	3.1	3.3	3.4	3.6	2.7	2.8	2.9	3.1	3.2	3.5	2.5	2.6	2.8	3.0	3.0	3.3
58.0		2.9/56.3	2.8	3.0	3.0	3.3	2.3	2.4	2.6	2.8	2.8	3.1	2.2	2.3	2.4	2.6	2.6	3.0
ロープ掛数	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1

主フォーム長さ(m) 補助ジブ長さ(m) 作業半径 (m)	57.90						60.95						64.00					
	12.20		18.30		24.40		12.20		18.30		24.40		12.20		18.30			
	オフセット角度 (°)						オフセット角度 (°)						オフセット角度 (°)					
	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30		
12.9																		
14.0																		
16.0	11.0/16.1						11.0/16.6						11.0/17.2					
18.0	11.0	8.0/19.1	10.0/18.6				11.0	8.0/19.6	10.0/19.2				11.0		10.0/19.7			
20.0	11.0	8.0	10.0		6.0/20.8		11.0	8.0	10.0		6.0/21.4		11.0	8.0/20.1	10.0			
22.0	11.0	8.0	10.0	6.0/22.9	6.0		11.0	8.0	10.0	6.0/23.4	6.0		11.0	8.0	10.0			
24.0	11.0	8.0	10.0	6.0	6.0		11.0	8.0	10.0	6.0	6.0		11.0	8.0	10.0	6.0		
26.0	11.0	8.0	10.0	6.0	6.0	4.5/26.5	11.0	8.0	10.0	6.0	6.0	4.5/27.0	10.2	8.0	9.9	6.0		
28.0	11.0	8.0	9.1	6.0	6.0	4.5	10.5	8.0	8.9	6.0	6.0	4.5	9.5	8.0	8.8	6.0		
30.0	9.8	8.0	8.5	6.0	6.0	4.5	9.7	8.0	8.3	6.0	6.0	4.5	8.8	8.0	8.1	6.0		
32.0	8.8	8.0	8.0	6.0	6.0	4.5	8.7	8.0	7.8	6.0	6.0	4.5	8.1	8.0	7.6	6.0		
34.0	7.9	8.0	7.6	6.0	6.0	4.5	7.8	8.0	7.3	6.0	6.0	4.5	7.5	8.0	7.1	6.0		
36.0	7.1	7.5	7.1	6.0	6.0	4.5	7.0	7.3	6.9	6.0	6.0	4.5	6.8	7.2	6.6	6.0		
38.0	6.5	6.7	6.6	6.0	6.0	4.5	6.3	6.6	6.4	6.0	6.0	4.5	6.2	6.5	6.2	6.0		
40.0	5.8	6.1	6.1	5.9	6.0	4.5	5.7	6.0	6.0	6.0	6.0	4.5	5.5	5.8	5.8	6.0		
42.0	5.3	5.5	5.6	5.8	5.8	4.5	5.1	5.4	5.4	5.8	5.6	4.5	4.9	5.2	5.3	5.7		
44.0	4.7	5.0	5.0	5.4	5.2	4.5	4.5	4.8	4.9	5.2	5.1	4.5	4.3	4.6	4.7	5.1		
46.0	4.2	4.5	4.5	4.9	4.8	4.5	4.0	4.3	4.3	4.8	4.6	4.5	3.8	4.1	4.1	4.6		
48.0	3.7	4.0	4.0	4.4	4.3	4.4	3.5	3.8	3.8	4.2	4.1	4.4	3.3	3.6	3.7	4.1		
50.0	3.3	3.5	3.6	3.9	3.8	4.3	3.1	3.3	3.4	3.8	3.6	4.2	2.9	3.1	3.2	3.6		
52.0	2.9	3.1	3.2	3.5	3.4	3.9	2.7	2.9	3.0	3.3	3.2	3.7	2.5	2.7	2.8	3.2		
54.0	2.5	2.7	2.8	3.1	3.0	3.5	2.3	2.5	2.6	2.9	2.9	3.3	2.1	2.3	2.4	2.8		
56.0	2.2	2.3	2.5	2.7	2.7	3.1	2.0	2.1	2.3	2.6	2.5	2.9		2.0	2.1	2.4		
58.0	1.9	2.0																

定格総荷重表

■補助ジブ付き主ブーム

(単位: t)

主ブーム長さ(m) 補助ジブ長さ(m) 作業半径 (m)	39.60						42.65						45.70					
	12.20		18.30		24.40		12.20		18.30		24.40		12.20		18.30		24.40	
	オフセット角度 (°)						オフセット角度 (°)						オフセット角度 (°)					
	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30
8.7	48.3	48.1	47.1	46.9	45.9	45.6												
9.0	47.9	47.7	46.7	46.5	45.5	45.2	43.5/9.2	43.4/9.2	42.4/9.2	42.1/9.2	41.1/9.2	40.8/9.2	39.4/9.8	39.2/9.8	38.2/9.8	38.0/9.8	37.0/9.8	36.7/9.8
10.0	46.6	46.5	45.5	45.3	44.3	44.0	42.6	42.4	41.5	41.2	40.2	39.9	39.2	39.0	38.0	37.8	36.9	36.5
12.0	36.2	36.0	35.6	35.2	34.9	34.3	36.2	35.9	35.6	35.1	34.9	34.3	36.1	35.8	35.4	35.0	34.8	34.1
14.0	28.8	28.5	28.2	27.8	27.5	27.0	28.7	28.5	28.1	27.8	27.5	27.0	28.6	28.4	28.0	27.6	27.4	26.9
16.0	23.5	23.4	23.0	22.7	22.4	22.0	23.5	23.3	22.9	22.7	22.3	21.9	23.3	23.2	22.8	22.5	22.2	21.8
18.0	19.7	19.5	19.1	18.9	18.6	18.2	19.6	19.5	19.1	18.9	18.5	18.2	19.5	19.3	19.0	18.7	18.4	18.0
20.0	16.7	16.6	16.2	16.0	15.6	15.4	16.7	16.5	16.2	16.0	15.6	15.3	16.5	16.4	16.0	15.8	15.5	15.2
22.0	14.4	14.3	13.9	13.7	13.3	13.1	14.3	14.2	13.8	13.7	13.3	13.0	14.2	14.1	13.7	13.5	13.1	12.9
24.0	12.5	12.4	12.0	11.9	11.5	11.3	12.4	12.3	11.9	11.8	11.4	11.2	12.3	12.2	11.8	11.6	11.3	11.0
26.0	10.9	10.9	10.4	10.3	9.9	9.8	10.8	10.8	10.4	10.3	9.9	9.7	10.7	10.6	10.2	10.1	9.7	9.5
28.0	9.6	9.6	9.2	9.1	8.6	8.5	9.5	9.5	9.1	9.0	8.6	8.4	9.4	9.3	8.9	8.8	8.4	8.2
30.0	8.5	8.5	8.0	8.0	7.5	7.4	8.4	8.4	8.0	7.9	7.4	7.3	8.2	8.2	7.8	7.7	7.3	7.2
32.0	7.6	7.5	7.1	7.0	6.6	6.5	7.4	7.4	7.0	6.9	6.5	6.4	7.3	7.2	6.8	6.8	6.3	6.2
34.0	6.7	6.7	6.3	6.3	5.8	5.7	6.6	6.6	6.2	6.1	5.6	5.5	6.4	6.4	6.0	5.9	5.4	5.3
36.0	6.1/35.8	6.1/35.8	5.7/35.8	5.6/35.8	5.1/35.8	5.0/35.8	5.9	5.9	5.4	5.4	4.8	4.8	5.7	5.7	5.2	5.1	4.6	4.5
38.0							5.2	5.2	4.7	4.7	4.1	4.1	5.0	5.0	4.5	4.4	3.9	3.8
40.0							5.1/38.5	5.0/38.5	4.5/38.5	4.5/38.5	4.0/38.5	3.9/38.5	4.4	4.3	3.8	3.8	3.3	3.2
42.0													4.0/41.1	4.0/41.1	3.5/41.1	3.5/41.1	3.0/41.1	2.9/41.1
44.0																		
ロープ掛数	5	5	5	5	5	5	4	4	4	4	4	4	4	4	4	4	4	4

主ブーム長さ(m) 補助ジブ長さ(m) 作業半径 (m)	48.75						51.80						54.85					
	12.20		18.30		24.40		12.20		18.30		24.40		12.20		18.30		24.40	
	オフセット角度 (°)						オフセット角度 (°)						オフセット角度 (°)					
	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30
8.7																		
9.0																		
10.0	33.0/10.3	33.0/10.3	33.0/10.3	33.0/10.3	33.0/10.3	32.6/10.3	32.1/10.8	32.0/10.8	31.0/10.8	30.7/10.8	29.8/10.8	29.4/10.8	29.1/11.3	28.9/11.3	28.0/11.3	27.7/11.3	26.8/11.3	26.4/11.3
12.0	33.0	33.0	32.8	32.6	31.6	31.3	31.3	31.1	30.2	29.9	28.9	28.5	28.7	28.5	27.6	27.3	26.4	25.9
14.0	28.5	28.3	27.9	27.6	27.3	26.8	28.3	28.1	27.8	27.4	27.2	26.6	27.5	27.3	26.3	26.1	25.1	24.7
16.0	23.2	23.1	22.7	22.4	22.1	21.7	23.1	22.9	22.6	22.3	22.0	21.5	22.9	22.7	22.4	22.1	21.9	21.4
18.0	19.4	19.2	18.9	18.6	18.3	17.9	19.2	19.0	18.7	18.4	18.2	17.8	19.1	18.9	18.6	18.3	18.0	17.6
20.0	16.4	16.3	15.9	15.7	15.4	15.1	16.2	16.1	15.7	15.5	15.2	14.9	16.1	15.9	15.6	15.4	15.1	14.8
22.0	14.0	13.9	13.6	13.4	13.0	12.8	13.9	13.8	13.4	13.2	12.9	12.6	13.7	13.6	13.2	13.1	12.7	12.5
24.0	12.1	12.0	11.7	11.5	11.1	10.9	12.0	11.9	11.5	11.3	11.0	10.8	11.8	11.7	11.3	11.2	10.8	10.6
26.0	10.6	10.5	10.1	9.9	9.6	9.4	10.4	10.3	9.9	9.8	9.4	9.2	10.2	10.1	9.8	9.6	9.3	9.1
28.0	9.2	9.1	8.8	8.6	8.3	8.1	9.0	9.0	8.6	8.5	8.1	7.9	8.9	8.8	8.4	8.3	8.0	7.8
30.0	8.1	8.0	7.6	7.5	7.2	7.0	7.9	7.9	7.5	7.4	7.0	6.8	7.8	7.7	7.3	7.2	6.8	6.6
32.0	7.1	7.1	6.7	6.6	6.1	6.0	6.9	6.9	6.5	6.4	5.9	5.8	6.8	6.7	6.3	6.2	5.7	5.6
34.0	6.3	6.2	5.8	5.7	5.2	5.1	6.1	6.0	5.6	5.5	5.0	4.8	5.9	5.8	5.4	5.3	4.8	4.6
36.0	5.5	5.4	4.9	4.9	4.4	4.3	5.3	5.2	4.7	4.6	4.2	4.0	5.0	5.0	4.5	4.4	4.0	3.8
38.0	4.7	4.7	4.2	4.2	3.7	3.6	4.5	4.5	4.0	3.9	3.4	3.3	4.3	4.2	3.8	3.7	3.2	3.1
40.0	4.1	4.1	3.6	3.5	3.0	3.0	3.9	3.8	3.3	3.3	2.8	2.7	3.6	3.6	3.1	3.1		
42.0	3.5	3.5	3.0	3.0			3.3	3.2	2.8	2.7			3.1	3.0				
44.0	3.1/43.7	3.0/43.7	2.6/43.7				2.8	2.7					2.5	2.5				
ロープ掛数	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3

主ブーム長さ(m) 補助ジブ長さ(m) 作業半径 (m)	48.75						51.80						54.85			
	12.20		18.30		24.40		12.20		18.30		24.40		12.20		18.30	
	オフセット角度 (°)						オフセット角度 (°)						オフセット角度 (°)			
	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30
8.7																
9.0																
10.0	26.2/11.9	26.0/11.9	25.1/11.9	24.8/11.9	23.9/11.9	23.4/11.9										
12.0	26.2	25.9	25.0	24.7	23.8	23.4	22.0/12.5	22.0/12.5	21.4	21.0	20.2	19.7	20.5	20.2	19.4	19.0
14.0	25.0	24.8	23.9	23.6	22.7	22.3	22.0	22.0	20.4	20.1	19.2	18.8	19.6	19.4	18.5	18.2
16.0	22.7	22.5	22.2	21.9	21.6	21.2	21.5	21.3	20.4	20.1	19.2	18.8	19.6	19.4	18.5	18.2
18.0	18.8	18.7	18.3	18.1	17.8	17.4	18.8	18.7	18.3	18.1	17.8	17.4	18.7	18.5	17.6	17.4
20.0	15.8	15.7	15.4	15.1	14.8	14.5	15.8	15.7	15.4	15.1	14.9	14.5	15.7	15.5	15.2	15.0
22.0	13.5	13.3	13.0	12.8	12.5	12.2	13.5	13.3	13.0	12.8	12.5	12.2	13.3	13.2	12.9	12.6
24.0	11.6	11.4	11.1	10.9	10.6	10.4	11.5	11.4	11.1	10.9	10.6	10.3	11.4	11.3	10.9	10.8
26.0	10.0	9.9	9.5	9.4	9.0	8.8	9.9	9.8	9.5	9.3	9.0	8.8	9.8	9.7	9.3	9.2
28.0	8.6	8.5	8.2	8.1	7.7	7.5	8.6	8.5	8.2	8.0	7.7	7.5	8.4	8.3	8.0	7.9
30.0	7.5	7.4	7.1	6.9	6.5	6.3	7.5	7.4	7.0	6.9	6.5	6.2	7.3	7.2	6.8	6.7
32.0	6.5	6.4	6.0	5.9	5.4	5.2	6.4	6.3	5.9	5.8	5.3	5.2	6.2	6.1	5.7	5.6
34.0	5.6	5.5	5.0	4.9	4.5	4.3	5.5	5.4	4.9	4.8	4.4	4.2	5.3	5.2	4.8	4.6
36.0	4.7	4.6	4.2	4.1	3.6	3.5	4.6	4.5	4.1	4.0	3.6	3.4	4.4	4.3	3.9	3.8
38.0	4.0	3.9	3.5	3.4	2.9		3.9	3.8	3.4	3.3			3.7	3.6	3.2	3.1
40.0	3.3	3.2	2.8				3.2	3.1					3.0	2.9		
42.0	2.7	2.7														
44.0																
ロープ掛数	3	3	3	3	3	3	2	2	2	2	2	2	2	2	2	2