

# 定格総荷重表

## ■28.65mタワー

(単位：t)

作業半径 (m)	タワージブ長さ (m)															
	22.85								25.90							
	タワー角度 (°)															
	90		80		70		60		90		80		70		60	
2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	
9.2	20.0	11.0/9.7														
10.0	20.0	11.0							18.6	11.0/10.5						
12.0	20.0	11.0							18.6	11.0						
14.0	20.0	11.0							18.6	11.0						
15.0	18.5	11.0							18.2	11.0						
16.0	17.2	11.0	16.5/16.7	11.0/17.3					17.0	11.0	15.0/17.9					
18.0	15.1	11.0	15.1	11.0					14.9	11.0	14.9	11.0/18.4				
20.0	13.5	11.0	13.5	11.0					13.3	11.0	13.3	11.0				
22.0	12.3	11.0	12.3	11.0					12.0	11.0	12.0	11.0				
24.0	10.2	10.2	11.2	11.0	10.8/24.9	10.5/25.6			11.0	11.0	11.0	11.0				
26.0	8.7/24.6	8.7/25.6	10.3	10.3	10.3	10.3			10.1	10.1	10.1	10.1	9.9/26.5	9.6/27.2		
28.0			9.6	9.6	9.6	9.6			7.6/27.5	7.6	9.3	9.3	9.3	9.3		
30.0			9.2/29.5	9.0	9.0	9.0			7.6/28.5	8.7	8.7	8.7	8.7	8.7		
32.0				8.9/30.5	8.4	8.4	8.2/32.3	8.0/33.1			8.1	8.1	8.1	8.1		
34.0					7.9	7.9	7.9	7.9			8.0/32.5	7.7/33.5	7.6	7.6	7.5/34.4	7.4/35.1
36.0					7.8/34.3	7.6/35.3	7.4	7.4					7.2	7.2	7.2	7.2
38.0							7.0	7.0					7.0/37.2	6.8	6.8	6.8
40.0							6.9/38.7	6.7/39.6						6.8/38.2	6.4	6.4
42.0															6.1/41.6	6.0
44.0																5.9/42.6

## ■31.70mタワー

作業半径 (m)	タワージブ長さ (m)															
	22.85								25.90							
	タワー角度 (°)															
	90		80		70		60		90		80		70		60	
2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	
9.2	20.0	11.0/9.7														
10.0	20.0	11.0							18.6	11.0/10.5						
12.0	20.0	11.0							18.6	11.0						
14.0	19.9	11.0							18.6	11.0						
15.0	18.4	11.0							18.2	11.0						
16.0	17.1	11.0	15.8/17.2	11.0/17.8					16.9	11.0						
18.0	15.0	11.0	15.0	11.0					14.8	11.0	14.5/18.4	11.0/19.0				
20.0	13.4	11.0	13.4	11.0					13.2	11.0	13.2	11.0				
22.0	12.1	11.0	12.1	11.0					11.9	11.0	11.9	11.0				
24.0	10.3	10.3	11.0	11.0	10.1/25.9				10.8	10.8	10.8	10.8				
26.0	8.8/24.6	8.8/25.6	10.1	10.1	10.1	9.9/26.6			9.9	9.9	9.9	9.9	9.4/27.5			
28.0			9.4	9.4	9.4	9.4			7.8/27.5	7.8	9.2	9.2	9.2	9.1/28.2		
30.0			8.7	8.7	8.7	8.7			7.8/28.5	8.5	8.5	8.5	8.5	8.5		
32.0				8.5/31.0	8.2	8.2	7.8/33.8				7.9	7.9	7.9	7.9		
34.0					7.7	7.7	7.7	7.6/34.6			7.7/33.0	7.4	7.4	7.4	7.0/35.9	
36.0					7.4/35.3	7.2	7.2	7.2				7.0	7.0	7.0	6.8/36.7	
38.0						7.1/36.3	6.8	6.8				6.5	6.5	6.5	6.5	
40.0							6.4	6.4				6.5/38.2	6.3/39.2	6.2	6.2	
42.0							6.4/40.2	6.2/41.2							5.8	5.8
44.0															5.6/43.1	5.5
46.0																5.4/44.1

作業半径 (m)	タワージブ長さ (m)							
	28.95							
	タワー角度 (°)							
	90		80		70		60	
2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	
9.2								
10.0	15.4/10.8	11.0/11.3						
12.0	15.4	11.0						
14.0	15.4	11.0						
15.0	15.4	11.0						
16.0	15.4	11.0						
18.0	14.6	11.0	13.4/19.5					
20.0	13.0	11.0	13.0	11.0/20.1				
22.0	11.7	11.0	11.7	11.7				
24.0	10.6	10.6	10.6	10.6				
26.0	9.7	9.7	9.7	9.7				
28.0	9.0	9.0	9.0	9.0	8.6/29.1	8.4/29.8		
30.0	7.4	7.4	8.3	8.3	8.3	8.3		
32.0	6.8/30.4	6.8/31.4	7.7	7.7	7.7	7.7		
34.0			7.2	7.2	7.2	7.2		
36.0			6.8/35.9	6.8	6.8	6.4/37.9		
38.0				6.6/36.9	6.4	6.4	6.3/38.7	
40.0					6.0	6.0	6.0	
42.0					5.8/41.2	5.6	5.6	
44.0						5.6/42.2	5.3	5.3
46.0							5.0	5.0
48.0							5.0/46.1	4.8/47.1

# 定格総荷重表

## ■34.75mタワー

(単位：t)

作業半径 (m)	タワージブ長さ (m)															
	22.85								25.90							
	タワー角度 (°)								タワー角度 (°)							
	90		80		70		60		90		80		70		60	
2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	
9.2	20.0	11.0/9.7								18.6	11.0/10.5					
10.0	20.0	11.0								18.6	11.0					
12.0	20.0	11.0								18.6	11.0					
14.0	19.8	11.0								18.1	11.0					
15.0	18.3	11.0								16.8	11.0					
16.0	17.0	11.0	15.1/17.8							14.7	11.0	13.9/18.9	11.0/19.5			
18.0	14.9	11.0	14.9	11.0/18.3						13.0	11.0	13.0	11.0			
20.0	13.2	11.0	13.2	11.0						11.7	11.0	11.7	11.0			
22.0	11.9	11.0	11.9	11.0						10.7	10.7	10.7	10.7			
24.0	10.4	10.4	10.9	10.9						9.8	9.8	9.8	9.8			
26.0	9.0/24.6	9.0/25.6	10.0	10.0	9.6/27.0	9.4/27.6				7.9/27.5	7.9	9.0	9.0	8.8/28.6	8.5/29.3	
28.0			9.2	9.2	9.2	9.2				7.9/28.5	8.3	8.3	8.3	8.3		
30.0			8.5	8.5	8.5	8.5				7.7	7.7	7.7	7.7			
32.0			8.3/30.6	8.0/31.6	7.9	7.9				7.3/33.5	7.2	7.2	7.2			
34.0					7.4	7.4	7.1/35.4									
36.0					6.9	6.9	6.9	6.9/36.2				7.1/34.5	6.8	6.8	6.5/37.4	
38.0					6.8/36.3	6.6/37.3	6.5	6.5					6.3	6.3	6.3	6.3/38.2
40.0							6.1	6.1					6.0/39.3	5.9	5.9	5.9
42.0							5.8/41.7	5.7						5.9/40.3	5.6	5.6
44.0								5.6/42.7							5.2	5.2
46.0															5.1/44.6	4.9/45.6

作業半径 (m)	タワージブ長さ (m)															
	28.95								32.00							
	タワー角度 (°)								タワー角度 (°)							
	90		80		70		60		90		80		70		60	
2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	
9.2																
10.0	15.4/10.8	11.0/11.3								14.6/11.6						
12.0	15.4	11.0								14.6	11.0/12.1					
14.0	15.4	11.0								14.6	11.0					
15.0	15.4	11.0								14.6	11.0					
16.0	15.4	11.0								14.6	11.0					
18.0	14.5	11.0								14.3	11.0					
20.0	12.9	11.0	12.8/20.1	11.0/20.6						12.7	11.0	11.9/21.2	11.0/21.8			
22.0	11.6	11.0	11.6	11.0						11.4	11.0	11.4	11.0			
24.0	10.5	10.5	10.5	10.5						10.4	10.4	10.4	10.4			
26.0	9.6	9.6	9.6	9.6						9.5	9.5	9.5	9.5			
28.0	8.8	8.8	8.8	8.8						8.7	8.7	8.7	8.7			
30.0	7.5	7.5	8.2	8.2	8.1/30.2	7.9/30.9				8.0	8.0	8.0	8.0	7.5/31.8		
32.0	6.9/30.4	6.9/31.4	7.6	7.6	7.6	7.6				7.4	7.4	7.4	7.4	7.4	7.3/32.5	
34.0			7.0	7.0	7.0	7.0				6.0/33.4	6.0	6.9	6.9	6.9	6.9	
36.0			6.6	6.6	6.6	6.6				6.0/34.4	6.5	6.5	6.5	6.5		
38.0			6.5/36.5	6.2/37.5	6.1	6.1	5.9/39.4				6.0	6.0	6.0	6.0		
40.0					5.8	5.8	5.8	5.8/40.2			5.7/39.4	5.6	5.6	5.6	5.4/41.5	
42.0					5.4	5.4	5.4	5.4				5.5/40.4	5.3	5.3	5.3	5.2/42.3
44.0					5.4/42.2	5.2/43.2	5.0	5.0					4.9	4.9	4.9	4.9
46.0							4.7	4.7					4.7/45.2	4.6	4.6	4.6
48.0							4.5/47.6	4.4						4.6/46.2	4.3	4.3
50.0								4.3/48.6							4.0	4.0
52.0															3.9/50.5	3.8/51.5

# 定格総荷重表

## ■37.80mタワー

作業半径 (m)	タワージブ長さ (m)																														
	22.85								25.90																						
	タワー角度 (°)																														
	90				80				70				60				90				80				70				60		
2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛				
9.2	20.0	11.0/9.7																													
10.0	20.0	11.0								18.6	11.0/10.5																				
12.0	20.0	11.0								18.6	11.0																				
14.0	19.8	11.0								18.6	11.0																				
15.0	18.2	11.0								18.0	11.0																				
16.0	16.9	11.0								16.7	11.0																				
18.0	14.8	11.0	14.5/18.3	11.0/18.9						14.6	11.0	13.4/19.4																			
20.0	13.1	11.0	13.1	11.0						12.9	11.0	12.9	11.0																		
22.0	11.8	11.0	11.8	11.0						11.6	11.0	11.6	11.0																		
24.0	10.5	10.5	10.7	10.7						10.6	10.6	10.6	10.6																		
26.0	9.1/24.6	9.1/25.6	9.8	9.8						9.7	9.7	9.7	9.7																		
28.0			9.1	9.1	9.1	8.9/28.7				8.0/27.5	8.0	8.9	8.9	8.3/29.6																	
30.0			8.4	8.4	8.4	8.4				8.0/28.5	8.2	8.2	8.2	8.1/30.3																	
32.0			8.1/31.1	7.8	7.8	7.8					7.6	7.6	7.6	7.6																	
34.0				7.8/32.1	7.3	7.3					7.1	7.1	7.1	7.1																	
36.0					6.8	6.8	6.5/36.9	6.4/37.7				6.9/35.0	6.6	6.6																	
38.0					6.5/37.4	6.3	6.3	6.3					6.2	6.2	5.9/38.9	5.7/39.7															
40.0						6.2/38.4	5.9	5.9					5.8	5.8	5.7	5.7															
42.0							5.5	5.5					5.7/40.3	5.5/41.3	5.3	5.3															
44.0							5.3/43.2	5.2							5.0	5.0															
46.0								5.2/44.2							4.7	4.7															
48.0															4.7/46.2	4.5/47.2															

# 定格総荷重表

## ■28.65mタワー

(単位：t)

作業半径 (m)	タワージブ長さ (m)															
	22.85								25.90							
	タワー角度 (°)															
	90		80		70		60		90		80		70		60	
2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	
9.2	20.0	11.0/9.7														
10.0	20.0	11.0							18.6	11.0/10.5						
12.0	20.0	11.0							18.6	11.0						
14.0	20.0	11.0							18.6	11.0						
15.0	18.5	11.0							18.2	11.0						
16.0	17.2	11.0	16.5/16.7	11.0/17.3					17.0	11.0	15.0/17.9					
18.0	15.1	11.0	15.1	11.0					14.9	11.0	14.9	11.0/18.4				
20.0	13.5	11.0	13.5	11.0					13.3	11.0	13.3	11.0				
22.0	12.3	11.0	12.3	11.0					12.0	11.0	12.0	11.0				
24.0	10.2	10.2	11.2	11.0	10.8/24.9	10.5/25.6			11.0	11.0	11.0	11.0				
26.0	8.7/24.6	8.7/25.6	10.3	10.3	10.3	10.3			10.1	10.1	10.1	10.1	9.9/26.5	9.6/27.2		
28.0			9.6	9.6	9.6	9.6			7.6/27.5	7.6	9.3	9.3	9.3	9.3		
30.0			9.2/29.5	9.0	9.0	9.0			7.6/28.5	8.7	8.7	8.7	8.7	8.7		
32.0				8.9/30.5	8.4	8.4	8.2/32.3	8.0/33.1			8.1	8.1	8.1	8.1		
34.0					7.9	7.9	7.9	7.9			8.0/32.5	7.7/33.5	7.6	7.6	7.5/34.4	7.4/35.1
36.0					7.8/34.3	7.6/35.3	7.4	7.4					7.2	7.2	7.2	7.2
38.0							7.0	7.0					7.0/37.2	6.8	6.8	6.8
40.0							6.9/38.7	6.7/39.6						6.8/38.2	6.4	6.4
42.0															6.1/41.6	6.0
44.0																5.9/42.6

## ■31.70mタワー

作業半径 (m)	タワージブ長さ (m)															
	22.85								25.90							
	タワー角度 (°)															
	90		80		70		60		90		80		70		60	
2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	
9.2	20.0	11.0/9.7														
10.0	20.0	11.0							18.6	11.0/10.5						
12.0	20.0	11.0							18.6	11.0						
14.0	19.9	11.0							18.6	11.0						
15.0	18.4	11.0							18.2	11.0						
16.0	17.1	11.0	15.8/17.2	11.0/17.8					16.9	11.0						
18.0	15.0	11.0	15.0	11.0					14.8	11.0	14.5/18.4	11.0/19.0				
20.0	13.4	11.0	13.4	11.0					13.2	11.0	13.2	11.0				
22.0	12.1	11.0	12.1	11.0					11.9	11.0	11.9	11.0				
24.0	10.3	10.3	11.0	11.0	10.1/25.9				10.8	10.8	10.8	10.8				
26.0	8.8/24.6	8.8/25.6	10.1	10.1	10.1	9.9/26.6			9.9	9.9	9.9	9.9	9.4/27.5			
28.0			9.4	9.4	9.4	9.4			7.8/27.5	7.8	9.2	9.2	9.2	9.1/28.2		
30.0			8.7	8.7	8.7	8.7			7.8/28.5	8.5	8.5	8.5	8.5	8.5		
32.0				8.5/31.0	8.2	8.2	7.8/33.8				7.9	7.9	7.9	7.9		
34.0					7.7	7.7	7.7	7.6/34.6			7.7/33.0	7.4	7.4	7.4	7.0/35.9	
36.0					7.4/35.3	7.2	7.2	7.2				7.0	7.0	7.0	6.8/36.7	
38.0						7.1/36.3	6.8	6.8				6.5	6.5	6.5	6.5	
40.0							6.4	6.4				6.5/38.2	6.3/39.2	6.2	6.2	
42.0							6.4/40.2	6.2/41.2							5.8	5.8
44.0															5.6/43.1	5.5
46.0																5.4/44.1

作業半径 (m)	タワージブ長さ (m)							
	28.95							
	タワー角度 (°)							
	90		80		70		60	
2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	
9.2								
10.0	15.4/10.8	11.0/11.3						
12.0	15.4	11.0						
14.0	15.4	11.0						
15.0	15.4	11.0						
16.0	15.4	11.0						
18.0	14.6	11.0	13.4/19.5					
20.0	13.0	11.0	13.0	11.0/20.1				
22.0	11.7	11.0	11.7	11.7				
24.0	10.6	10.6	10.6	10.6				
26.0	9.7	9.7	9.7	9.7				
28.0	9.0	9.0	9.0	9.0	8.6/29.1	8.4/29.8		
30.0	7.4	7.4	8.3	8.3	8.3	8.3		
32.0	6.8/30.4	6.8/31.4	7.7	7.7	7.7	7.7		
34.0			7.2	7.2	7.2	7.2		
36.0			6.8/35.9	6.8	6.8	6.8	6.4/37.9	
38.0				6.6/36.9	6.4	6.4	6.4	6.3/38.7
40.0					6.0	6.0	6.0	6.0
42.0					5.8/41.2	5.6	5.6	5.6
44.0						5.6/42.2	5.3	5.3
46.0							5.0	5.0
48.0							5.0/46.1	4.8/47.1

# 定格総荷重表

## ■34.75mタワー

(単位：t)

作業半径 (m)	タワージブ長さ (m)															
	22.85								25.90							
	タワー角度 (°)								タワー角度 (°)							
	90		80		70		60		90		80		70		60	
2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	
9.2	20.0	11.0/9.7								18.6	11.0/10.5					
10.0	20.0	11.0								18.6	11.0					
12.0	20.0	11.0								18.6	11.0					
14.0	19.8	11.0								18.1	11.0					
15.0	18.3	11.0								16.8	11.0					
16.0	17.0	11.0	15.1/17.8							14.7	11.0	13.9/18.9	11.0/19.5			
18.0	14.9	11.0	14.9	11.0/18.3						13.0	11.0	13.0	11.0			
20.0	13.2	11.0	13.2	11.0						11.7	11.0	11.7	11.0			
22.0	11.9	11.0	11.9	11.0						10.7	10.7	10.7	10.7			
24.0	10.4	10.4	10.9	10.9						9.8	9.8	9.8	9.8			
26.0	9.0/24.6	9.0/25.6	10.0	10.0	9.6/27.0	9.4/27.6				7.9/27.5	7.9	9.0	9.0	8.8/28.6	8.5/29.3	
28.0			9.2	9.2	9.2	9.2				7.9/28.5	8.3	8.3	8.3	8.3		
30.0			8.5	8.5	8.5	8.5				7.7	7.7	7.7	7.7			
32.0			8.3/30.6	8.0/31.6	7.9	7.9				7.3/33.5	7.2	7.2	7.2			
34.0					7.4	7.4	7.1/35.4									
36.0					6.9	6.9	6.9	6.9/36.2				7.1/34.5	6.8	6.8	6.5/37.4	
38.0					6.8/36.3	6.6/37.3	6.5	6.5					6.3	6.3	6.3	6.3/38.2
40.0							6.1	6.1					6.0/39.3	5.9	5.9	5.9
42.0							5.8/41.7	5.7						5.9/40.3	5.6	5.6
44.0								5.6/42.7							5.2	5.2
46.0															5.1/44.6	4.9/45.6

作業半径 (m)	タワージブ長さ (m)																
	28.95								32.00								
	タワー角度 (°)								タワー角度 (°)								
	90		80		70		60		90		80		70		60		
2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛		
9.2																	
10.0	15.4/10.8	11.0/11.3								14.6/11.6							
12.0	15.4	11.0								14.6	11.0/12.1						
14.0	15.4	11.0								14.6	11.0						
15.0	15.4	11.0								14.6	11.0						
16.0	15.4	11.0								14.6	11.0						
18.0	14.5	11.0								14.3	11.0						
20.0	12.9	11.0	12.8/20.1	11.0/20.6						12.7	11.0	11.9/21.2	11.0/21.8				
22.0	11.6	11.0	11.6	11.0						11.4	11.0	11.4	11.0				
24.0	10.5	10.5	10.5	10.5						10.4	10.4	10.4	10.4				
26.0	9.6	9.6	9.6	9.6						9.5	9.5	9.5	9.5				
28.0	8.8	8.8	8.8	8.8						8.7	8.7	8.7	8.7				
30.0	7.5	7.5	8.2	8.2	8.1/30.2	7.9/30.9				8.0	8.0	8.0	8.0	7.5/31.8			
32.0	6.9/30.4	6.9/31.4	7.6	7.6	7.6	7.6				7.4	7.4	7.4	7.4	7.4	7.3/32.5		
34.0			7.0	7.0	7.0	7.0				6.0/33.4	6.0	6.9	6.9	6.9	6.9		
36.0			6.6	6.6	6.6	6.6					6.0/34.4	6.5	6.5	6.5	6.5		
38.0			6.5/36.5	6.2/37.5	6.1	6.1	5.9/39.4					6.0	6.0	6.0	6.0		
40.0					5.8	5.8	5.8	5.8/40.2				5.7/39.4	5.6	5.6	5.6	5.4/41.5	
42.0					5.4	5.4	5.4	5.4					5.5/40.4	5.3	5.3	5.3	5.2/42.3
44.0					5.4/42.2	5.2/43.2	5.0	5.0						4.9	4.9	4.9	4.9
46.0							4.7	4.7						4.7/45.2	4.6	4.6	4.6
48.0							4.5/47.6	4.4							4.6/46.2	4.3	4.3
50.0								4.3/48.6								4.0	4.0
52.0																3.9/50.5	3.8/51.5

# 定格総荷重表

## ■37.80mタワー

作業半径 (m)	タワージブ長さ (m)																														
	22.85								25.90																						
	タワー角度 (°)																														
	90				80				70				60				90				80				70				60		
2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛				
9.2	20.0	11.0/9.7																													
10.0	20.0	11.0								18.6	11.0/10.5																				
12.0	20.0	11.0								18.6	11.0																				
14.0	19.8	11.0								18.6	11.0																				
15.0	18.2	11.0								18.0	11.0																				
16.0	16.9	11.0								16.7	11.0																				
18.0	14.8	11.0	14.5/18.3	11.0/18.9						14.6	11.0	13.4/19.4																			
20.0	13.1	11.0	13.1	11.0						12.9	11.0	12.9	11.0																		
22.0	11.8	11.0	11.8	11.0						11.6	11.0	11.6	11.0																		
24.0	10.5	10.5	10.7	10.7						10.6	10.6	10.6	10.6																		
26.0	9.1/24.6	9.1/25.6	9.8	9.8						9.7	9.7	9.7	9.7																		
28.0			9.1	9.1	9.1	8.9/28.7				8.0/27.5	8.0	8.9	8.9	8.3/29.6																	
30.0			8.4	8.4	8.4	8.4				8.0/28.5	8.2	8.2	8.2	8.1/30.3																	
32.0			8.1/31.1	7.8	7.8	7.8					7.6	7.6	7.6	7.6																	
34.0				7.8/32.1	7.3	7.3					7.1	7.1	7.1	7.1																	
36.0					6.8	6.8	6.5/36.9	6.4/37.7				6.9/35.0	6.6	6.6																	
38.0					6.5/37.4	6.3	6.3	6.3					6.2	6.2	5.9/38.9	5.7/39.7															
40.0						6.2/38.4	5.9	5.9					5.8	5.8	5.7	5.7															
42.0							5.5	5.5					5.7/40.3	5.5/41.3	5.3	5.3															
44.0							5.3/43.2	5.2							5.0	5.0															
46.0								5.2/44.2							4.7	4.7															
48.0															4.7/46.2	4.5/47.2															

# 定格総荷重表

(単位:t)

作業半径 (m)	タワージブ長さ (m)															
	28.95								32.00							
	タワー角度 (°)															
	90		80		70		60		90		80		70		60	
2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	
9.2																
10.0	15.4/10.8	11.0/11.3							14.6/11.6							
12.0	15.4	11.0							14.6	11.0/12.1						
14.0	15.4	11.0							14.6	11.0						
15.0	15.4	11.0							14.6	11.0						
16.0	15.4	11.0							14.6	11.0						
18.0	14.4	11.0							14.3	11.0						
20.0	12.8	11.0	12.4/20.6	11.0/21.2					12.6	11.0	11.5/21.7					
22.0	11.5	11.0	11.5	11.0					11.3	11.0	11.3	11.0/22.3				
24.0	10.4	10.4	10.4	10.4					10.3	10.3	10.3	10.3				
26.0	9.5	9.5	9.5	9.5					9.4	9.4	9.4	9.4				
28.0	8.7	8.7	8.7	8.7					8.6	8.6	8.6	8.6				
30.0	7.6	7.6	8.0	8.0	7.7/31.2	7.5/31.9			7.9	7.9	7.9	7.9				
32.0	7.0/30.4	7.0/31.4	7.5	7.5	7.5	7.5			7.4	7.4	7.4	7.4	7.2/32.8	7.0/33.5		
34.0			6.9	6.9	6.9	6.9			6.1/33.4	6.1	6.8	6.8	6.8	6.8		
36.0			6.5	6.5	6.5	6.5			6.1/34.4	6.4	6.4	6.4	6.4	6.4		
38.0			6.3/37.0	6.0	6.0	6.0				5.9	5.9	5.9	5.9	5.9		
40.0					5.6	5.6	5.4/41.0	5.2/41.8			5.5/39.9	5.5	5.5	5.5		
42.0					5.3	5.3	5.2	5.2			5.4/40.9	5.2	5.2	4.9/43.0	4.7/43.8	
44.0					5.0/43.3	4.9	4.9	4.9				4.8	4.8	4.7	4.7	
46.0						4.9/44.3	4.6	4.6				4.5	4.5	4.5	4.5	
48.0							4.3	4.3				4.5/46.2	4.3/47.2	4.2	4.2	
50.0							4.1/49.1	4.0						3.9	3.9	
52.0								4.0/50.1						3.6	3.6	
54.0														3.6/52.1	3.5/53.1	

作業半径 (m)	タワージブ長さ (m)							
	35.05							
	タワー角度 (°)							
	90		80		70		60	
2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	
9.2								
10.0								
12.0	12.5/12.4	11.0/12.9						
14.0	12.5	11.0						
15.0	12.5	11.0						
16.0	12.5	11.0						
18.0	12.5	11.0						
20.0	12.5	11.0						
22.0	11.2	11.0	10.7/22.9	10.4/23.4				
24.0	10.1	10.1	10.1	10.1				
26.0	9.2	9.2	9.2	9.2				
28.0	8.5	8.5	8.5	8.5				
30.0	7.8	7.8	7.8	7.8				
32.0	7.2	7.2	7.2	7.2				
34.0	6.7	6.7	6.7	6.7	6.6/34.5	6.4/35.1		
36.0	5.3	5.3	6.2	6.2	6.2	6.2		
38.0	5.3/36.3	5.3/37.3	5.8	5.8	5.8	5.8		
40.0			5.4	5.4	5.4	5.4		
42.0			5.0	5.0	5.0	5.0		
44.0			4.9/42.9	4.7/43.9	4.7	4.7	4.4/45.0	4.3/45.8
46.0					4.4	4.4	4.3	4.3
48.0					4.1	4.1	4.0	4.0
50.0					3.9/49.2	3.8	3.8	3.8
52.0						3.8/50.2	3.5	3.5
54.0							3.2	3.2
56.0							3.1/55.0	3.0

# 定格総荷重表

## ■40.85mタワー

作業半径 (m)	タワージブ長さ (m)															
	22.85 タワー角度 (°)							25.90 タワー角度 (°)								
	90		80		70		60		90		80		70		60	
	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛
9.2	17.5	11.0/9.7														
10.0	17.5	11.0						16.0	11.0/10.5							
12.0	17.5	11.0						16.0	11.0							
14.0	17.5	11.0						16.0	11.0							
15.0	17.5	11.0						16.0	11.0							
16.0	16.8	11.0						16.0	11.0							
18.0	14.7	11.0	14.0/18.8	11.0/19.4				14.5	11.0							
20.0	13.0	11.0	13.0	11.0				12.8	11.0	12.8	11.0/20.5					
22.0	11.7	11.0	11.7	11.0				11.5	11.0	11.5	11.0					
24.0	10.3	10.3	10.6	10.6				10.4	10.4	10.4	10.4					
26.0	9.1/24.6	9.1/25.6	9.7	9.7				9.5	9.5	9.5	9.5					
28.0			8.9	8.9	8.6/29.0	8.3/29.7		8.0/27.5	8.0	8.7	8.7					
30.0			8.2	8.2	8.2	8.2		8.0/28.5	8.0	8.0	7.8/30.7	7.6/31.3				
32.0			7.7/31.6	7.6	7.6	7.6			7.4	7.4	7.4	7.4				
34.0			7.5/32.6	7.1	7.1	7.1			6.9	6.9	6.9	6.9				
36.0				6.6	6.6	6.6			6.8/34.6	6.5/35.6	6.4	6.4				
38.0				6.1	6.1	5.8/38.4	5.7/39.2				6.0	6.0				
40.0				6.0/38.4	5.8/39.4	5.5	5.5				5.6	5.6	5.3/40.4	5.2/41.2		
42.0						5.2	5.2				5.3/41.4	5.2	5.0	5.0		
44.0						4.8	4.8					5.1/42.4	4.7	4.7		
46.0						4.7/44.8	4.6/45.7						4.4	4.4		
48.0													4.2/47.7	4.2		
50.0														4.1/48.7		

(単位：t)

作業半径 (m)	タワージブ長さ (m)															
	28.95 タワー角度 (°)							32.00 タワー角度 (°)								
	90		80		70		60		90		80		70		60	
	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛
9.2																
10.0	15.0/10.8	11.0/11.3						14.0/11.6								
12.0	15.0	11.0						14.0	11.0/12.1							
14.0	15.0	11.0						14.0	11.0							
15.0	15.0	11.0						14.0	11.0							
16.0	15.0	11.0						14.0	11.0							
18.0	14.3	11.0						14.0	11.0							
20.0	12.7	11.0	12.0/21.1	11.0/21.7				12.6	11.0							
22.0	11.4	11.0	11.4	11.0				11.2	11.0	11.1/22.3	10.8/22.8					
24.0	10.3	10.3	10.3	10.3				10.2	10.2	10.2	10.2					
26.0	9.4	9.4	9.4	9.4				9.3	9.3	9.3	9.3					
28.0	8.6	8.6	8.6	8.6				8.5	8.5	8.5	8.5					
30.0	7.3	7.3	7.9	7.9				7.8	7.8	7.8	7.8					
32.0	6.7/30.4	6.7/31.4	7.3	7.3	7.2/32.3	7.1/33.0		7.2	7.2	7.2	7.2	7.0/33.9				
34.0			6.8	6.8	6.8	6.8		5.8/33.4	5.8	6.7	6.7	6.7	6.6/34.6			
36.0			6.3	6.3	6.3	6.3			5.8/34.4	6.2	6.2	6.2	6.2			
38.0			6.0/37.5	5.9	5.9	5.9				5.8	5.8	5.8	5.8			
40.0				5.8/38.5	5.5	5.5				5.4	5.4	5.4	5.4			
42.0					5.1	5.1	4.8/42.5	4.7/43.3		5.3/40.5	5.1/41.5	5.0	5.0			
44.0					4.7	4.7	4.5	4.5				4.7	4.7	4.3/44.5	4.2/45.3	
46.0					4.7/44.3	4.5/45.3	4.3	4.3				4.3	4.3	4.1	4.1	
48.0							4.0	4.0				4.1/47.3	4.0	3.9	3.9	
50.0							3.8	3.8					4.0/48.3	3.7	3.7	
52.0							3.7/50.6	3.5/51.6						3.4	3.4	
54.0														3.2/53.6	3.2	
56.0															3.1/54.6	



# 定格総荷重表

作業半径 (m)	タワージフ長さ (m)														
	35.05							38.10							
	タワー角度 (°)														
	90		80		70		60		90		80		70		60
2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛
9.2															
10.0															
12.0	12.5/12.4	11.0/12.9						11.0/13.2	11.0/13.6						
14.0	12.5	11.0						11.0	11.0						
15.0	12.5	11.0						11.0	11.0						
16.0	12.5	11.0						11.0	11.0						
18.0	12.5	11.0						11.0	11.0						
20.0	12.4	11.0						11.0	11.0						
22.0	11.1	11.0	10.3/23.4					11.0	11.0						
24.0	10.0	10.0	10.0	10.0				10.0	10.0	9.8/24.5	9.5/25.1				
26.0	9.1	9.1	9.1	9.1				9.0	9.0	9.0	9.0				
28.0	8.4	8.4	8.4	8.4				8.3	8.3	8.3	8.3				
30.0	7.7	7.7	7.7	7.7				7.6	7.6	7.6	7.6				
32.0	7.1	7.1	7.1	7.1				7.0	7.0	7.0	7.0				
34.0	6.6	6.6	6.6	6.6	6.2/35.5			6.5	6.5	6.5	6.5				
36.0	5.4	5.4	6.1	6.1	6.1	6.1/36.2		6.1	6.1	6.1	6.1	5.8/37.1	5.6/37.8		
38.0	5.0/36.3	5.0/37.3	5.7	5.7	5.7	5.7		5.4	5.4	5.6	5.6	5.6	5.6		
40.0			5.3	5.3	5.3	5.3		4.3/39.3	4.3	5.3	5.3	5.3	5.3		
42.0			4.9	4.9	4.9	4.9			4.3/40.3	4.9	4.9	4.9	4.9		
44.0			4.7/43.4	4.6	4.6	4.6				4.6	4.6	4.6	4.6		
46.0				4.5/44.4	4.3	4.3	3.9/46.6	3.8/47.4		4.3	4.3	4.3	4.3		
48.0					4.0	4.0	3.7	3.7		4.3/46.3	4.1/47.3	4.0	4.0	3.5/48.6	3.4/49.4
50.0					3.8	3.8	3.5	3.5				3.8	3.8	3.4	3.4
52.0					3.8/50.2	3.6/51.2	3.3	3.3				3.5	3.5	3.2	3.2
54.0							3.1	3.1				3.4/53.1	3.3	3.0	3.0
56.0							2.8	2.8					3.3/54.1	2.8	2.8
58.0							2.7/56.5	2.6/57.5						2.5	2.5
60.0														2.4/59.5	2.3
62.0															2.2/60.5

# 定格総荷重表

## ■43.90mタワー

(単位：t)

作業半径 (m)	タワージブ長さ (m)															
	22.85								25.90							
	タワー角度 (°)								タワー角度 (°)							
	90		80		70		60		90		80		70		60	
2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	
9.2	17.5	11.0/9.7														
10.0	17.5	11.0							16.0	11.0/10.5						
12.0	17.5	11.0							16.0	11.0						
14.0	17.5	11.0							16.0	11.0						
15.0	17.5	11.0							16.0	11.0						
16.0	16.7	11.0							16.0	11.0						
18.0	14.6	11.0	13.4/19.4	11.0/19.9					14.4	11.0						
20.0	12.9	11.0	12.9	11.0					12.8	11.0	12.5/20.5	11.0/21.1				
22.0	11.6	11.0	11.6	11.0					11.4	11.0	11.4	11.0				
24.0	10.3	10.3	10.5	10.5					10.3	10.3	10.3	10.3				
26.0	8.8/24.6	8.8/25.6	9.6	9.6					9.4	9.4	9.4	9.4				
28.0			8.8	8.8					7.7/27.5	7.7	8.6	8.6				
30.0			8.1	8.1	8.1/30.1	7.9/30.8			7.7/28.5	8.0	8.0	7.5/31.7				
32.0			7.5	7.5	7.5	7.5				7.4	7.4	7.4	7.3/32.4			
34.0			7.4/32.2	7.1/33.2	6.9	6.9				6.8	6.8	6.8	6.8			
36.0					6.5	6.5				6.5/35.1	6.3	6.3	6.3			
38.0					6.0	6.0	5.2/39.9				6.3/36.1	5.9	5.9			
40.0					5.7/39.5	5.6	5.2	5.1/40.7				5.5	5.5			
42.0						5.5/40.5	4.9	4.9				5.1	5.1	4.7	4.6/42.8	
44.0							4.6	4.6				5.0/42.4	4.8/43.4	4.4	4.4	
46.0							4.3	4.3						4.1	4.1	
48.0							4.2/46.3	4.2/47.3						3.9	3.9	
50.0														3.7/49.2	3.7	
52.0															3.7/50.2	

作業半径 (m)	タワージブ長さ (m)															
	28.95								32.00							
	タワー角度 (°)								タワー角度 (°)							
	90		80		70		60		90		80		70		60	
2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	
9.2																
10.0	15.0/10.8	11.0/11.3							14.0/11.6							
12.0	15.0	11.0							14.0	11.0/12.1						
14.0	15.0	11.0							14.0	11.0						
15.0	15.0	11.0							14.0	11.0						
16.0	15.0	11.0							14.0	11.0						
18.0	14.3	11.0							14.0	11.0						
20.0	12.6	11.0	11.6/21.6						12.5	11.0						
22.0	11.3	11.0	11.3	11.0/22.2					11.2	11.0	10.8/22.8	10.4/23.4				
24.0	10.2	10.2	10.2	10.2					10.1	10.1	10.1	10.1				
26.0	9.3	9.3	9.3	9.3					9.2	9.2	9.2	9.2				
28.0	8.5	8.5	8.5	8.5					8.4	8.4	8.4	8.4				
30.0	7.4	7.4	7.8	7.8					7.7	7.7	7.7	7.7				
32.0	6.7/30.4	6.7/31.4	7.2	7.2	6.9/33.3				7.1	7.1	7.1	7.1				
34.0			6.7	6.7	6.7	6.7			5.8/33.4	5.8	6.6	6.6	6.4/34.9	6.2/35.6		
36.0			6.2	6.2	6.2	6.2				5.8/34.4	6.2	6.2	6.2	6.2		
38.0			5.8	5.8	5.8	5.8					5.7	5.7	5.7	5.7		
40.0				5.6/39.0	5.4	5.4					5.3	5.3	5.3	5.3		
42.0					5.0	5.0				5.2/41.0	5.0	5.0	5.0			
44.0					4.6	4.6	4.2	4.1/44.8				4.6	4.6			
46.0					4.4/45.4	4.3	4.0	4.0				4.3	4.3	3.8	3.7/46.8	
48.0						4.2/46.4	3.7	3.7				4.0	4.0	3.6	3.6	
50.0							3.5	3.5				3.9/48.3	3.7/49.3	3.4	3.4	
52.0							3.3	3.3						3.2	3.2	
54.0							3.3/52.2	3.3/53.2						3.0	3.0	
56.0														2.9/55.1	2.9	
58.0															2.9/56.1	

# 定格総荷重表

(単位: t)

作業半径 (m)	タワージブ長さ (m)																
	35.05								38.10								
	タワー角度 (°)																
	90		80		70		60		90		80		70		60		
2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛		
9.2																	
10.0																	
12.0	12.5/12.4	11.0/12.9								11.0/13.2	11.0/13.6						
14.0	12.5	11.0								11.0	11.0						
15.0	12.5	11.0								11.0	11.0						
16.0	12.5	11.0								11.0	11.0						
18.0	12.5	11.0								11.0	11.0						
20.0	12.4	11.0								11.0	11.0						
22.0	11.1	11.0	10.1/23.9							11.0	11.0						
24.0	10.0	10.0	10.0	9.8/24.5						9.9	9.9	9.4/25.1	9.2/25.6				
26.0	9.1	9.1	9.1	9.1						9.0	9.0	9.0	9.0				
28.0	8.3	8.3	8.3	8.3						8.3	8.3	8.3	8.3				
30.0	7.7	7.7	7.7	7.7						7.6	7.6	7.6	7.6				
32.0	7.1	7.1	7.1	7.1						7.0	7.0	7.0	7.0				
34.0	6.6	6.6	6.6	6.6						6.5	6.5	6.5	6.5				
36.0	5.4	5.4	6.1	6.1	6.0/36.5	5.9/37.2				6.1	6.1	6.1	6.1				
38.0	5.1/36.3	5.1/37.3	5.7	5.7	5.7	5.7				5.4	5.4	5.6	5.6	5.6/38.2	5.5/38.8		
40.0			5.3	5.3	5.3	5.3				4.4/39.3	4.4	5.3	5.3	5.3	5.3		
42.0			4.9	4.9	4.9	4.9					4.4/40.3	4.9	4.9	4.9	4.9		
44.0			4.6/43.9	4.6	4.6	4.6						4.6	4.6	4.6	4.6		
46.0				4.5/44.9	4.3	4.3						4.3	4.3	4.3	4.3		
48.0					4.0	4.0	3.4/48.1	3.3/48.9				4.2/46.9	4.0/47.9	4.0	4.0		
50.0					3.8	3.8	3.2	3.2						3.8	3.8	3.1/50.1	3.0/50.9
52.0					3.6/51.2	3.5	3.0	3.0						3.5	3.5	2.9	2.9
54.0						3.5/52.2	2.8	2.8						3.3	3.3	2.7	2.7
56.0							2.7	2.7						3.3/54.2	3.1/55.2	2.5	2.5
58.0							2.5	2.5								2.3	2.3
60.0							2.4/58.1	2.3/59.0								2.2	2.2
62.0																2.1/61.0	2.1

作業半径 (m)	タワージブ長さ (m)							
	41.15							
	タワー角度 (°)							
	90		80		70		60	
2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	
9.2								
10.0								
12.0								
14.0	10.0	10.0/14.4						
15.0	10.0	10.0						
16.0	10.0	10.0						
18.0	10.0	10.0						
20.0	10.0	10.0						
22.0	9.8	9.8						
24.0	9.2	9.2						
26.0	8.6	8.6	8.9/26.2	8.7/26.8				
28.0	8.0	8.0	8.3	8.3				
30.0	7.3	7.3	7.6	7.6				
32.0	6.7	6.7	7.0	7.0				
34.0	6.1	6.1	6.5	6.5				
36.0	5.2	5.2	6.1	6.1				
38.0	4.6	4.6	5.6	5.6	5.3/39.8			
40.0	4.4	4.4	5.3	5.3	5.3	5.2/40.5		
42.0	4.0	4.0	4.9	4.9	4.9	4.9		
44.0	3.8/42.2	3.7/43.2	4.6	4.6	4.6	4.6		
46.0			4.3	4.3	4.3	4.3		
48.0			4.0	4.0	4.0	4.0		
50.0			3.8/49.8	3.8	3.8	3.8		
52.0				3.7/50.8	3.5	3.5	2.7/52.2	2.6/53.0
54.0					3.3	3.3	2.5	2.5
56.0					3.0	3.0	2.3	2.3
58.0					2.9/57.1	2.9	2.2	2.2
60.0						2.8/58.1	2.0	2.0
62.0							1.9	1.9
64.0							1.8/63.0	1.7

# 定格総荷重表

## ■46.95mタワー

(単位：t)

作業半径 (m)	タワージブ長さ (m)															
	22.85								25.90							
	タワー角度 (°)				タワー角度 (°)				タワー角度 (°)				タワー角度 (°)			
	90		80		70		60		90		80		70		60	
	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛
9.2	17.5	11.0/9.7														
10.0	17.5	11.0							16.0	11.0/10.5						
12.0	17.5	11.0							16.0	11.0						
14.0	17.5	11.0							16.0	11.0						
15.0	17.5	11.0							16.0	11.0						
16.0	16.7	11.0							16.0	11.0						
18.0	14.5	11.0	12.9/19.9						14.4	11.0						
20.0	12.8	11.0	12.8	11.0/20.5					12.7	11.0	12.1/21.0	11.0/21.6				
22.0	11.5	11.0	11.5	11.0					11.4	11.0	11.4	11.0				
24.0	10.4	10.4	10.4	10.4					10.3	10.3	10.3	10.3				
26.0	8.9/24.6	8.9/25.6	9.5	9.5					9.4	9.4	9.4	9.4				
28.0			8.7	8.7					7.7/27.5	7.7	8.6	8.6				
30.0			8.0	8.0	7.7/31.1	7.5/31.8			7.7/28.5	7.9	7.9					
32.0			7.4	7.4	7.4	7.4				7.3	7.3	7.1/32.7	6.9/33.4			
34.0			7.2/32.7	6.9/33.7	6.8	6.8				6.7	6.7	6.7	6.7			
36.0					6.3	6.3				6.4/35.6	6.3	6.3	6.3			
38.0					5.9	5.9					6.2/36.6	5.8	5.8			
40.0					5.4	5.4	4.6/41.5					5.4	5.4			
42.0					5.3/40.5	5.2/41.5	4.5	4.5/42.2				5.0	5.0	4.2/43.5		
44.0							4.3	4.3				4.8/43.5	4.7	4.1	4.1/44.3	
46.0							4.0	4.0					4.6/44.5	3.8	3.8	
48.0							3.8/47.8	3.8						3.6	3.6	
50.0								3.8/48.8						3.4	3.4	
52.0														3.3/50.7	3.3/51.7	

作業半径 (m)	タワージブ長さ (m)															
	28.95								32.00							
	タワー角度 (°)				タワー角度 (°)				タワー角度 (°)				タワー角度 (°)			
	90		80		70		60		90		80		70		60	
	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛
9.2																
10.0	15.0/10.8	11.0/11.3							14.0/11.6							
12.0	15.0	11.0							14.0	11.0/12.1						
14.0	15.0	11.0							14.0	11.0						
15.0	15.0	11.0							14.0	11.0						
16.0	15.0	11.0							14.0	11.0						
18.0	14.2	11.0							14.0	11.0						
20.0	12.6	11.0							12.5	11.0						
22.0	11.2	11.0	11.1/22.2	10.8/22.7					11.2	11.0	10.5/23.3	10.2/23.9				
24.0	10.2	10.2	10.2	10.2					10.1	10.1	10.1	10.1				
26.0	9.2	9.2	9.2	9.2					9.2	9.2	9.2	9.2				
28.0	8.5	8.5	8.5	8.5					8.4	8.4	8.4	8.4				
30.0	7.4	7.4	7.8	7.8					7.7	7.7	7.7	7.7				
32.0	6.8/30.4	6.8/31.4	7.2	7.2					7.1	7.1	7.1	7.1				
34.0			6.7	6.7	6.6/34.4	6.5/35.0			5.8/33.4	5.8	6.6	6.6				
36.0			6.2	6.2	6.2	6.2				5.8/34.4	6.2	6.2	6.2	6.0/36.7		
38.0			5.8	5.8	5.8	5.8					5.7	5.7	5.7	5.7		
40.0			5.7/38.6	5.5/39.6	5.4	5.4					5.3	5.3	5.3	5.3		
42.0					5.0	5.0					5.1/41.5	5.0	5.0	5.0		
44.0					4.6	4.6	3.7/45.5					4.9/42.5	4.6	4.6		
46.0					4.3	4.3	3.7	3.7/46.3					4.3	4.3	3.4/47.6	
48.0					4.2/46.4	4.1/47.4	3.4	3.4					4.0	4.0	3.3	3.3/48.4
50.0							3.2	3.2					3.9/49.3	3.8	3.1	3.1
52.0							3.0	3.0						3.8/50.3	2.9	2.9
54.0							2.9/53.7	2.9							2.7	2.7
56.0								2.9/54.7							2.5	2.5
58.0															2.5/56.6	2.5/57.6