

# クローラクレーン

■クレーンブーム定格総荷重表

(単位：t)

作業半径(m)	ブーム長さ(m)													
	18.30	21.35	24.40	27.45	30.50	33.50	36.55	39.60	42.65	45.70	48.75	51.80	54.85	57.90
5.0	100.0/5.1													
5.5	100.0	90.0/5.7												
6.0	90.8	90.0	80.0	70.0/6.7										
7.0	75.1	75.0	74.9	70.0	60.0/7.2	53.1/7.7								
8.0	60.6	61.0	60.8	60.7	60.0	52.7	50.0/8.3	42.4/8.8						
9.0	50.6	52.1	52.0	51.8	51.7	50.1	50.0	42.1	40.0/9.3	40.0/9.8				
10.0	43.4	45.4	45.3	45.1	45.0	44.8	44.6	40.8	40.0	40.0	30.0/10.3	30.0/10.9	25.0/11.4	25.0/11.9
12.0	33.7	36.0	35.9	35.7	35.5	35.4	35.2	35.0	34.8	34.7	30.0	30.0	25.0	25.0
14.0	27.4	29.4	29.2	29.1	28.9	28.7	28.5	28.4	28.2	28.0	27.8	27.7	25.0	25.0
16.0	22.9	24.4	24.2	24.1	23.9	23.7	23.5	23.3	23.2	23.0	22.8	22.6	22.4	22.3
18.0	21.2/17.3	21.0	20.8	20.6	20.5	20.3	20.1	19.9	19.7	19.5	19.3	19.2	19.0	18.8
20.0		19.0	18.0	17.8	17.7	17.5	17.3	17.1	16.9	16.7	16.6	16.4	16.2	16.0
22.0			15.8	15.7	15.6	15.4	15.2	15.0	14.8	14.6	14.4	14.3	14.1	13.9
24.0			15.3/22.5	13.9	13.7	13.6	13.4	13.2	13.0	12.8	12.6	12.4	12.2	12.1
26.0				13.1/25.0	12.2	12.1	11.9	11.7	11.5	11.3	11.1	10.9	10.7	10.5
28.0					11.3/27.5	10.9	10.7	10.5	10.3	10.1	9.9	9.7	9.5	9.3
30.0						9.9	9.5	9.3	9.1	8.9	8.7	8.5	8.3	8.1
32.0						9.7/30.4	8.6	8.4	8.2	8.0	7.8	7.6	7.4	7.3
34.0							8.2/33.0	7.6	7.4	7.2	7.1	6.9	6.8	6.6
36.0								7.1/35.6	6.9	6.7	6.5	6.4	6.2	6.0
38.0									6.4	6.2	6.0	5.8	5.6	5.4
40.0									6.3/38.3	5.7	5.5	5.3	5.1	4.9
42.0										5.4/40.9	5.1	4.8	4.6	4.4
44.0											4.7/43.5	4.3	4.2	3.9
46.0												3.9	3.8	3.5
48.0												3.9/46.2	3.4	3.1
50.0													3.3/48.8	2.8
52.0														2.5/51.5

作業半径(m)	ブーム長さ(m)				
	60.95	64.00	67.05	70.10	73.15
12.0	20.0/12.4	20.0/12.9	18.0/13.5		
14.0	20.0	20.0	18.0	16.0	15.7/14.5
16.0	20.0	20.0	18.0	16.0	14.5
18.0	18.6	18.4	16.2	15.0	13.0
20.0	15.8	15.6	15.4	13.5	11.7
22.0	13.7	13.5	13.3	12.3	10.5
24.0	11.9	11.7	11.5	11.3	9.6
26.0	10.4	10.2	10.0	9.8	8.8
28.0	9.1	9.0	8.8	8.6	8.0
30.0	7.9	7.8	7.7	7.5	7.3
32.0	7.1	7.0	6.8	6.7	6.5
34.0	6.5	6.3	6.1	5.9	5.7
36.0	5.8	5.6	5.4	5.2	5.0
38.0	5.2	5.0	4.8	4.6	4.4
40.0	4.7	4.5	4.3	4.1	3.9
42.0	4.2	4.0	3.8	3.6	3.4
44.0	3.7	3.5	3.3	3.0	2.8
46.0	3.3	3.0	2.8	2.6	
48.0	2.9	2.6	2.4		
50.0	2.5	2.3			
52.0	2.2				

[注意項目]

1. 本表に示す定格総荷重は水平堅土上における値で転倒荷重の78%以内および移動式クレーン構造規格で定める前方安定度が1.15以上の両方を満足する値です。
2. 実際に吊り上げ得る荷重は本表の値からフック(主フック)、バケット、吊り具一切の重量を差し引いた値となります。
3. 作業を行う場合は必ず、ハイマストにしてください。
4. 本表はカウンターウエイト重量43.7tの場合です。

■ショートジブ定格総荷重表

作業半径 (m)	ブーム長さ (m)													
	18.30	21.35	24.40	27.45	30.50	33.50	36.55	39.60	42.65	45.70	48.75	51.80	54.85	57.90
5.5	11.0/5.8													
6.0	11.0	11.0/6.3	11.0/6.8											
7.0	11.0	11.0	11.0	11.0/7.4	11.0/7.9									
8.0	11.0	11.0	11.0	11.0	11.0	11.0/8.4	11.0/8.9							
9.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0/9.4						
10.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0/10.5	11.0/11.0	11.0/11.5		
12.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0/12.6
14.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0
16.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0
18.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0
20.0	11.0/18.3	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0
22.0		11.0/21.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0
24.0			11.0/23.6	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0/25.8	11.0/25.6	11.0/25.3
26.0				11.0	11.0	11.0/27.8	11.0/27.5	11.0/27.1	11.0/26.8	11.0/26.5	11.0/26.1	10.9	10.7	10.5
28.0				11.0/26.3	11.0	10.9	10.7	10.5	10.3	10.1	9.9	9.7	9.5	9.3
30.0					10.7/28.9	9.9	9.5	9.3	9.1	8.9	8.7	8.5	8.3	8.1
32.0						9.0/31.6	8.6	8.4	8.2	8.0	7.8	7.6	7.4	7.3
34.0							7.8	7.6	7.4	7.2	7.1	6.9	6.8	6.6
36.0							7.7/34.2	6.9	6.9	6.7	6.5	6.4	6.2	6.0
38.0								6.7/36.8	6.4	6.2	6.0	5.8	5.6	5.4
40.0									6.0/39.5	5.7	5.5	5.3	5.1	4.9
42.0										5.2	5.1	4.8	4.6	4.4
44.0											4.6	4.3	4.2	3.9
46.0											4.4/44.8	3.9	3.8	3.5
48.0												3.6/47.4	3.4	3.1
50.0													3.0	2.8
52.0														2.4

■ショートジブ付き主ブーム定格総荷重表

作業半径 (m)	ブーム長さ (m)													
	18.30	21.35	24.40	27.45	30.50	33.50	36.55	39.60	42.65	45.70	48.75	51.80	54.85	57.90
5.0	100.0/5.1													
5.5	100.0	88.0/5.7												
6.0	90.8	88.0	80.0	70.0/6.7										
7.0	74.4	74.3	74.2	69.3	60.0/7.2	53.3/7.7								
8.0	59.9	60.3	60.1	60.0	59.3	52.7	50.0/8.3	42.4/8.8						
9.0	49.9	51.4	51.3	51.1	51.0	49.4	49.3	42.1	40.0/9.3	40.0/9.8				
10.0	42.7	44.7	44.6	44.4	44.3	44.1	43.9	40.1	40.0	40.0	30.0/10.3	30.0/10.9	25.0/11.4	25.0/11.9
12.0	33.0	35.3	35.2	35.0	34.8	34.7	34.5	34.3	34.1	34.0	30.0	30.0	25.0	25.0
14.0	26.7	28.7	28.5	28.4	28.2	28.0	27.8	27.7	27.5	27.3	27.1	27.0	24.3	24.3
16.0	22.2	23.7	23.5	23.4	23.2	23.0	22.8	22.6	22.5	22.3	22.1	21.9	21.7	21.6
18.0	20.5/17.3	20.3	20.1	19.9	19.8	19.6	19.4	19.2	19.0	18.8	18.6	18.5	18.3	18.1
20.0		18.3	17.3	17.1	17.0	16.8	16.6	16.4	16.2	16.0	15.9	15.7	15.5	15.3
22.0			15.1	15.0	14.9	14.7	14.5	14.3	14.1	13.9	13.7	13.6	13.4	13.2
24.0			14.7/22.5	13.2	13.0	12.9	12.7	12.5	12.3	12.1	11.9	11.7	11.5	11.4
26.0				12.4/25.0	11.5	11.4	11.2	11.0	10.8	10.6	10.4	10.2	10.0	9.8
28.0					10.6/27.5	10.2	10.0	9.8	9.6	9.4	9.2	9.0	8.8	8.6
30.0						9.2	8.8	8.6	8.4	8.2	8.0	7.8	7.6	7.4
32.0						9.0/30.4	7.9	7.7	7.5	7.3	7.1	6.9	6.7	6.6
34.0							7.5/33.0	6.9	6.7	6.5	6.4	6.2	6.1	5.9
36.0								6.3/35.6	6.2	6.0	5.8	5.7	5.5	5.3
38.0									5.7	5.5	5.3	5.1	4.9	4.7
40.0									5.6/38.3	5.0	4.8	4.6	4.4	4.2
42.0										4.7/40.9	4.4	4.2	3.9	3.7
44.0											4.0/43.5	3.6	3.5	3.2
46.0												3.2	3.1	2.8
48.0												3.2/46.2	2.7	2.4
50.0													2.4/48.8	

(単位：t)

ブーム長さ(m)			
60.95	64.00	67.05	70.10
11.0/13.2	11.0/13.7		
11.0	11.0	11.0/14.2	11.0/14.7
11.0	11.0	11.0	11.0
11.0	11.0	11.0	11.0
11.0	11.0	11.0	11.0
11.0	11.0	11.0	11.0/22.5
11.0/25.2	11.0/24.9	11.0/24.6	10.3
10.4	10.2	10.0	9.5
9.1	9.0	8.8	8.5
7.9	7.8	7.7	7.5
7.1	7.0	6.8	6.7
6.5	6.3	6.1	5.9
5.8	5.6	5.4	5.2
5.2	5.0	4.8	4.6
4.7	4.5	4.3	4.1
4.2	4.0	3.8	3.6
3.7	3.5	3.3	3.0
3.3	3.0	2.8	2.6
2.9	2.6	2.4	
2.5	2.3		
2.2			

【注意事項】

1. 本表に示す定格総荷重は水平堅土上における値で転倒荷重の78%以内および移動式クレーン構造規格で定める前方安定度が1.15以上の両方を満足する値です。
2. 実際に吊り上げ得る荷重は本表の値からフック(主フック+補フック)、玉掛けロープ等吊り具一切の重量を差し引いた値となります。
3. 作業を行う場合は必ず、ハイマストにしてください。
4. 本表はカウンターウエイト重量43.7tの場合です。

(単位：t)

ブーム長さ(m)			
60.95	64.00	67.05	70.10
20.0/12.4	20.0/12.9	18.0/13.5	
20.0	20.0	18.0	16.0
19.3	19.3	18.0	16.0
17.9	17.7	15.5	14.3
15.1	14.9	14.7	12.8
13.0	12.8	12.6	11.6
11.2	11.0	10.8	10.6
9.7	9.5	9.3	9.1
8.4	8.3	8.1	7.9
7.2	7.1	7.0	6.8
6.4	6.3	6.1	6.0
5.8	5.6	5.4	5.2
5.1	4.9	4.7	4.5
4.5	4.3	4.1	3.9
4.0	3.8	3.6	3.4
3.5	3.3	3.1	2.9
3.0	2.8	2.6	
2.6			

【注意事項】

1. 本表に示す定格総荷重は水平堅土上における値で転倒荷重の78%以内および移動式クレーン構造規格で定める前方安定度が1.15以上の両方を満足する値です。
2. 実際に吊り上げ得る荷重は本表の値からフック(主フック)、玉掛けロープ等吊り具一切の重量を差し引いた値となります。
3. ショートジブは補フック付きです。
4. 作業を行う場合は必ず、ハイマストにしてください。
5. 本表はカウンターウエイト重量43.7tの場合です。

■補助ジブ定格総荷重表

(単位：t)

ブーム長さ(m) ジブ長さ(m) オフセット角(deg) 作業半径(m)	39.60						42.65						45.70						
	12.20		18.30		24.40		12.20		18.30		24.40		12.20		18.30		24.40		
	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	
12.0	11.0/12.7																		
14.0	11.0	8.0/15.9	10.0/14.8					11.0/13.3						11.0			10.0/15.8		
16.0	11.0	8.0	10.0			6.0/16.6		11.0	8.0/16.5	10.0			6.0/17.1		11.0	8.0/17.0	10.0		6.0/17.7
18.0	11.0	8.0	10.0	6.0/19.7	6.0			11.0	8.0	10.0			6.0		11.0	8.0	10.0		6.0
20.0	11.0	8.0	10.0	6.0	6.0			11.0	8.0	10.0	6.0/20.2	6.0		11.0	8.0	10.0	6.0/20.7		6.0
22.0	11.0	8.0	10.0	6.0	6.0	4.5/23.1		11.0	8.0	10.0	6.0	6.0	4.5/23.6	11.0	8.0	10.0	6.0	6.0	6.0
24.0	11.0	8.0	10.0	6.0	6.0	4.5		11.0	8.0	10.0	6.0	6.0	4.5	11.0/25.8	8.0	10.0	6.0	6.0	4.5/24.1
26.0	11.0/26.4	8.0	10.0	6.0	6.0	4.5		11.0	8.0	10.0/27.8	6.0	6.0	4.5	10.9	8.0	10.0/27.5	6.0	6.0	4.5
28.0	10.1	8.0	10.0/28.2	6.0	6.0	4.5	9.9	8.0	9.9	6.0	6.0	4.5	9.7	8.0	9.7	6.0	6.0	4.5	4.5
30.0	9.1	8.0	9.1	6.0	6.0	4.5	8.9	8.0	8.9	6.0	6.0	4.5	8.8	8.0/31.8	8.8	6.0	6.0	4.5	4.5
32.0	8.3	8.0/32.8	8.3	6.0	6.0	4.5	8.1	8.0/32.3	8.1	6.0	6.0	4.5	7.9	7.9	7.9	6.0	6.0	4.5	4.5
34.0	7.6	7.6	7.6	6.0	6.0	4.5	7.4	7.4	7.4	6.0	6.0	4.5	7.2	7.2	7.2	6.0	6.0	4.5	4.5
36.0	6.9	6.9	6.9	6.0	6.0	4.5	6.7	6.7	6.7	6.0	6.0	4.5	6.6	6.6	6.6	6.0	6.0	4.5	4.5
38.0	6.4	6.4	6.4	6.0/39.6	6.0/39.6	4.5	6.2	6.2	6.2	6.0/38.8	6.0/38.8	4.5	6.0	6.0	6.0	6.0	6.0	4.5	4.5
40.0	5.9	5.9	5.9	5.9	5.9	4.5	5.7	5.7	5.7	5.7	5.7	4.5	5.5	5.5	5.5	5.5	5.5	4.5	4.5
42.0	5.4	5.4	5.4	5.4	5.4	4.5	5.2	5.2	5.2	5.2	5.2	4.5	5.0	5.0	5.0	5.0	5.0	4.5	4.5
44.0	5.0	5.0	5.0	5.0	5.0	4.5	4.8	4.8	4.8	4.8	4.8	4.5/45.5	4.6	4.6	4.6	4.6	4.6	4.5/44.5	4.5
46.0	4.6	4.6	4.6	4.6	4.6	4.5/46.5	4.4	4.4	4.4	4.4	4.4	4.4	4.2	4.2	4.2	4.2	4.2	4.2	4.2
48.0	4.3/47.3	4.2	4.2	4.2	4.2	4.2	4.0	4.0	4.0	4.0	4.0	4.0	3.8	3.8	3.8	3.8	3.8	3.8	3.8
50.0		4.2/48.1	3.8	3.8	3.8	3.8	3.6	3.6	3.6	3.6	3.6	3.6	3.4	3.4	3.4	3.4	3.4	3.4	3.4
52.0			3.4	3.4	3.4	3.4		3.5/50.7	3.2	3.2	3.2	3.2	3.0	3.0	3.0	3.0	3.0	3.0	3.0
54.0			3.2/53.1	3.0	3.0	3.0			2.8	2.8	2.8	2.8	2.9/52.6	2.8/53.4	2.7	2.7	2.7	2.7	2.7

ブーム長さ(m) ジブ長さ(m) オフセット角(deg) 作業半径(m)	48.75						51.80						54.85						
	12.20		18.30		24.40		12.20		18.30		24.40		12.20		18.30		24.40		
	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	
14.0	11.0/14.3							11.0/14.8						11.0/15.4					
16.0	11.0	8.0/17.5	10.0/16.4					11.0		10.0/16.9				11.0		10.0/17.4			
18.0	11.0	8.0	10.0			6.0/18.2		11.0	8.0	10.0			6.0/18.7		11.0	8.0/18.6	10.0		6.0/19.3
20.0	11.0	8.0	10.0	6.0/21.3	6.0			11.0	8.0	10.0	6.0/21.8	6.0		11.0	8.0	10.0			6.0
22.0	11.0	8.0	10.0	6.0	6.0			11.0	8.0	10.0	6.0	6.0		11.0	8.0	10.0	6.0/22.3		6.0
24.0	11.0/25.6	8.0	10.0	6.0	6.0	4.5/24.7	11.0/25.3	8.0	10.0		6.0	6.0	4.5/25.2	11.0/25.1	8.0	10.0	6.0	6.0	4.5/25.7
26.0	10.7	8.0	10.0/27.3	6.0	6.0	4.5	10.5	8.0	10.0/26.9	6.0	6.0	4.5	10.4	8.0	10.0/26.7	6.0	6.0	4.5	4.5
28.0	9.6	8.0	9.6	6.0	6.0	4.5	9.4	8.0	9.4	6.0	6.0	4.5	9.2	8.0	9.2	6.0	6.0	4.5	4.5
30.0	8.6	8.0/31.5	8.6	6.0	6.0	4.5	8.4	8.0/31.0	8.4	6.0	6.0	4.5	8.3	8.0/30.7	8.3	6.0	6.0	4.5	4.5
32.0	7.8	7.8	7.8	6.0	6.0	4.5	7.6	7.6	7.6	6.0	6.0	4.5	7.4	7.4	7.4	6.0	6.0	4.5	4.5
34.0	7.1	7.1	7.1	6.0	6.0	4.5	6.9	6.9	6.9	6.0	6.0	4.5	6.7	6.7	6.7	6.0	6.0	4.5	4.5
36.0	6.4	6.4	6.4	6.0/37.6	6.0/37.6	4.5	6.2	6.2	6.2	6.0/36.8	6.0/36.8	4.5	6.1	6.1	6.1	6.0/36.3	6.0/36.3	4.5	4.5
38.0	5.9	5.9	5.9	5.9	5.9	4.5	5.7	5.7	5.7	5.7	5.7	4.5	5.5	5.5	5.5	5.5	5.5	4.5	4.5
40.0	5.4	5.4	5.4	5.4	5.4	4.5	5.2	5.2	5.2	5.2	5.2	4.5	5.0	5.0	5.0	5.0	5.0	4.5	4.5
42.0	4.9	4.9	4.9	4.9	4.9	4.5	4.7	4.7	4.7	4.7	4.7	4.5/43.0	4.6	4.6	4.6	4.6	4.6	4.5/42.5	4.5
44.0	4.5	4.5	4.5	4.5	4.5	4.5	4.3	4.3	4.3	4.3	4.3	4.3	4.2	4.2	4.2	4.2	4.2	4.2	4.2
46.0	4.1	4.1	4.1	4.1	4.1	4.1	3.9	3.9	3.9	3.9	3.9	3.9	3.8	3.8	3.8	3.8	3.8	3.8	3.8
48.0	3.7	3.7	3.7	3.7	3.7	3.7	3.5	3.5	3.5	3.5	3.5	3.5	3.4	3.4	3.4	3.4	3.4	3.4	3.4
50.0	3.3	3.3	3.3	3.3	3.3	3.3	3.1	3.1	3.1	3.1	3.1	3.1	3.0	3.0	3.0	3.0	3.0	3.0	3.0
52.0	2.9	2.9	2.9	2.9	2.9	2.9	2.7	2.7	2.7	2.7	2.7	2.7	2.6	2.6	2.6	2.6	2.6	2.6	2.6
54.0	2.6	2.6	2.6	2.6	2.6	2.6	2.4	2.4	2.4	2.4	2.4	2.4	2.3	2.3	2.3	2.3	2.3	2.3	2.3

ブーム長さ(m) ジブ長さ(m) オフセット角(deg) 作業半径(m)	57.90						60.95						64.00					
	12.20		18.30		24.40		12.20		18.30		24.40		12.20		18.30			
	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30		
14.0	11.0/15.9																	
16.0	11.0		10.0/17.9												11.0/17.0			
18.0	11.0	8.0/19.1	10.0			6.0/19.8		11.0	8.0/19.6	10.0/18.5				11.0		10.0/19.0		
20.0	11.0	8.0	10.0			6.0		11.0	8.0	10.0			6.0/20.3		11.0	8.0/20.2	10.0	
22.0	11.0	8.0	10.0	6.0/22.9	6.0			11.0	8.0	10.0	6.0/23.4	6.0		11.0	8.0	10.0	6.0/23.9	
24.0	11.0/24.8	8.0	10.0	6.0	6.0			11.0/24.5	8.0	10.0	6.0	6.0		11.0/24.3	8.0	10.0/25.8	6.0	
26.0	10.2	8.0	10.0/26.3	6.0	6.0	4.5/26.2		10.0	8.0	10.0	6.0	6.0	4.5/26.8	9.9	8.0	9.9	6.0	
28.0	9.1	8.0	9.1	6.0	6.0	4.5	8.9	8.0/29.8	8.9	6.0	6.0	4.5	8.7	8.0/29.5	8.7	6.0	6.0	
30.0	8.1	8.0/30.2	8.1	6.0	6.0	4.5	7.9	7.9	7.9	6.0	6.0	4.5	7.8	7.8	7.8	6.0	6.0	
32.0	7.3	7.3	7.3	6.0	6.0	4.5	7.1	7.1	7.1	6.0	6.0	4.5	6.9	6.9	6.9	6.0	6.0	
34.0	6.6	6.6	6.6	6.0/35.7	6.0/35.7	4.5	6.4	6.4	6.4	6.0/35.1	6.0/35.1	4.5	6.2	6.2	6.2	6.0/34.6	6.0/34.6	
36.0	5.9	5.9	5.9	5.9	5.9	4.5	5.7	5.7	5.7	5.7	5.7	4.5	5.6	5.6	5.6	5.6	5.6	
38.0	5.4	5.4	5.4	5.4	5.4	4.5	5.2	5.2	5.2	5.2	5.2	4.5	5.0	5.0	5.0	5.0	5.0	
40.0	4.9	4.9	4.9	4.9	4.9	4.5/41.6	4.7	4.7	4.7	4.7	4.7	4.5/40.8	4.5	4.5	4.5	4.5	4.5	
42.0	4.4	4.4	4.4	4.4	4.4	4.4	4.2	4.2	4.2	4.2	4.2	4.2	3.9	3.9	3.9	3.9	3.9	
44.0	3.9	3.9	3.9	3.9	3.9	3.9	3.7	3.7	3.7	3.7	3.7	3.7	3.5	3.5	3.5	3.5	3.5	
46.0	3.5	3.5	3.5	3.5	3.5	3.5	3.3	3.3	3.3	3.3	3.3	3.3	3.0	3.0	3.0	3.0	3.0	
48.0	3.1	3.1	3.1	3.1	3.1	3.1	2.9	2.9	2.9	2.9	2.9	2.9	2.6	2.6	2.6	2.6	2.6	
50.0	2.8	2.8	2.8	2.8	2.8	2.8	2.5	2.5	2.5	2.5	2.5	2.5	2.3	2.3	2.3	2.3	2.3	
52.0	2.4	2.4	2.4	2.4	2.4	2.4	2.2	2.2	2.2	2.2	2.2	2.2	2.0	2.0	2.0	2.0	2.0	
54.0	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.0	2.0	2.0	2.0	2.0	

- 【注意項目】
1. 本表に示す定格総荷重は水平堅土における値で転倒荷重の78%以内および移動式クレーン構造規格で定める前方安定度が1.15以上の両方を満足する値です。
  2. 実際に吊り上げ得る荷重は上表の値からフック(主フック+補フック)、玉掛けロープ等吊り具一切の重量を差し引いた値となります。
  3. 作業を行う場合は必ず、ハイマストにしてください。
  4. 本表はカウンターウエイト重量43.7tの場合です。

■補助ジブ付き主ブーム定格総荷重表

(単位：t)

ブーム長さ(m)	39.60						42.65						45.70						
	12.20		18.30		24.40		12.20		18.30		24.40		12.20		18.30		24.40		
	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	
8.8	42.4	42.4	42.4	42.4	42.4	42.4													
9.0	42.1	42.1	42.1	42.1	42.1	42.1	38.1/9.3	38.1/9.3	38.1/9.3	38.1/9.3	38.1/9.3	38.1/9.3	33.9/9.8	33.9/9.8	33.9/9.8	33.9/9.8	33.9/9.8	33.9/9.8	33.9/9.8
10.0	40.8	40.8	40.5	40.0	40.0	39.2	36.7	36.7	36.7	36.7	36.7	36.7	33.7	33.7	33.7	33.7	33.7	33.7	33.7
12.0	31.3	31.0	30.8	30.4	30.3	29.7	31.2	31.0	30.8	30.3	30.3	29.7	31.1	30.9	30.7	30.3	30.2	29.6	29.6
14.0	25.0	24.8	24.5	24.2	24.1	23.6	24.9	24.7	24.5	24.1	24.0	23.5	24.8	24.6	24.4	24.0	23.9	23.4	23.4
16.0	20.6	20.4	20.1	19.9	19.7	19.3	20.5	20.3	20.1	19.8	19.6	19.2	20.4	20.2	20.0	19.7	19.5	19.1	19.1
18.0	17.3	17.2	16.9	16.7	16.4	16.1	17.2	17.1	16.8	16.6	16.3	16.0	17.1	17.0	16.7	16.5	16.2	15.9	15.9
20.0	14.8	14.7	14.4	14.2	13.9	13.6	14.7	14.6	14.3	14.1	13.8	13.5	14.6	14.5	14.2	14.0	13.7	13.4	13.4
22.0	12.8	12.7	12.4	12.2	11.9	11.7	12.7	12.6	12.3	12.1	11.8	11.6	12.6	12.5	12.2	12.0	11.7	11.5	11.5
24.0	11.2	11.1	10.8	10.6	10.3	10.1	11.1	11.0	10.7	10.5	10.2	10.0	11.0	10.9	10.6	10.4	10.1	9.9	9.9
26.0	9.8	9.7	9.4	9.2	8.9	8.7	9.7	9.6	9.3	9.1	8.8	8.6	9.6	9.5	9.2	9.0	8.7	8.5	8.5
28.0	8.7	8.6	8.3	8.2	7.8	7.7	8.6	8.5	8.2	8.1	7.7	7.6	8.5	8.4	8.1	8.0	7.6	7.5	7.5
30.0	7.7	7.6	7.3	7.2	6.8	6.6	7.6	7.5	7.2	7.1	6.7	6.6	7.5	7.4	7.1	7.0	6.6	6.4	6.4
32.0	6.9	6.8	6.4	6.3	5.8	5.7	6.8	6.7	6.3	6.2	5.8	5.6	6.7	6.6	6.2	6.0	5.6	5.4	5.4
34.0	6.1	6.0	5.6	5.5	5.0	4.8	6.0	5.9	5.5	5.3	4.9	4.7	5.8	5.7	5.3	5.2	4.7	4.5	4.5
36.0	5.4/35.6	5.3/35.6	5.0/35.6	4.9/35.6	4.3/35.6	4.1/35.6	5.2	5.1	4.7	4.6	4.1	4.0	5.0	4.9	4.5	4.4	4.0	3.8	3.8
38.0							4.5	4.4	4.0	3.9	3.4	3.3	4.3	4.2	3.8	3.7	3.3	3.1	3.1
40.0							4.4/38.3	4.3/38.3	3.9/38.3	3.8/38.3	3.3/38.3	3.2/38.3	3.7	3.6	3.2	3.1	2.7	2.6	2.6
42.0													3.4/40.9	3.3/40.9	2.9/40.9	2.8/40.9			

ブーム長さ(m)	48.75						51.80						54.85						
	12.20		18.30		24.40		12.20		18.30		24.40		12.20		18.30		24.40		
	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	
10.0	30.6/10.3	30.6/10.3	30.6/10.3	30.6/10.3	30.6/10.3	30.6/10.3	27.6/10.9	27.6/10.9	27.6/10.9	27.6/10.9	27.6/10.9	27.6/10.9	25.0/11.4	25.0/11.4	25.0/11.4	25.0/11.4	25.0/11.4	25.0/11.4	25.0/11.4
12.0	28.5	28.5	28.5	28.5	28.5	28.5	26.8	26.8	26.8	26.8	26.8	26.8	24.5	24.5	24.5	24.5	24.5	24.5	24.5
14.0	24.7	24.5	24.2	23.8	23.7	23.2	24.6	24.4	24.0	23.6	23.5	23.0	22.9	22.9	22.9	22.9	22.9	22.9	22.9
16.0	20.2	20.1	19.8	19.5	19.3	18.9	20.0	19.9	19.6	19.3	19.1	18.7	19.9	19.8	19.5	19.2	19.0	18.6	18.6
18.0	16.9	16.8	16.5	16.3	16.0	15.7	16.7	16.6	16.3	16.1	15.8	15.5	16.6	16.5	16.3	16.0	15.7	15.4	15.4
20.0	14.4	14.3	14.0	13.8	13.5	13.2	14.2	14.1	13.8	13.6	13.3	13.0	14.1	14.0	13.7	13.5	13.2	12.9	12.9
22.0	12.4	12.3	12.0	11.8	11.5	11.3	12.2	12.1	11.8	11.6	11.3	11.1	12.1	12.0	11.7	11.5	11.2	11.0	11.0
24.0	10.8	10.7	10.4	10.2	9.9	9.7	10.6	10.5	10.2	10.0	9.7	9.5	10.5	10.4	10.1	9.9	9.6	9.4	9.4
26.0	9.4	9.3	9.0	8.8	8.5	8.3	9.2	9.1	8.8	8.6	8.3	8.1	9.1	9.0	8.7	8.5	8.2	8.0	8.0
28.0	8.3	8.2	7.9	7.8	7.4	7.2	8.1	8.0	7.7	7.6	7.2	7.1	8.0	7.9	7.6	7.5	7.1	7.0	7.0
30.0	7.3	7.2	6.9	6.7	6.3	6.1	7.1	7.0	6.7	6.6	6.2	6.0	7.0	6.9	6.6	6.5	6.1	5.9	5.9
32.0	6.4	6.3	5.9	5.7	5.3	5.1	6.3	6.2	5.8	5.7	5.3	5.0	6.1	6.0	5.7	5.5	5.1	4.9	4.9
34.0	5.5	5.4	5.0	4.9	4.4	4.2	5.4	5.3	4.9	4.8	4.4	4.2	5.2	5.1	4.8	4.6	4.2	4.0	4.0
36.0	4.7	4.6	4.2	4.1	3.7	3.5	4.6	4.5	4.1	4.0	3.6	3.4	4.4	4.3	4.0	3.8	3.4	3.2	3.2
38.0	4.0	3.9	3.5	3.4	3.0		3.9	3.8	3.5	3.3	2.9		3.7	3.6	3.3	3.1			
40.0	3.4	3.3	2.9	2.8			3.3	3.2	2.8	2.7			3.1	3.0	2.7				
42.0	2.9	2.8					2.7	2.6					2.6						

ブーム長さ(m)	57.90						60.95						64.00						
	12.20		18.30		24.40		12.20		18.30		24.40		12.20		18.30				
	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30			
10.0	22.0/11.9	22.0/11.9	22.0/11.9	22.0/11.9	22.0/11.9	22.0/11.9	19.5/12.4	19.5/12.4	19.5/12.4	19.5/12.4	19.5/12.4	19.5/12.4	19.2/12.9	19.2/12.9	19.2/12.9	19.2/12.9			
12.0	21.9	21.9	21.9	21.9	21.9	21.9	18.7	18.7	18.7	18.7	18.7	18.7	18.5	18.5	18.5	18.5			
14.0	20.7	20.7	20.7	20.7	20.7	20.7	17.7	17.7	17.7	17.7	17.7	17.7	17.3	17.3	17.3	17.3			
16.0	19.7	19.7	19.4	19.1	19.0	18.5	17.7	17.7	17.7	17.7	17.7	17.7	17.3	17.3	17.3	17.3			
18.0	16.5	16.4	16.2	15.9	15.8	15.3	16.4	16.3	16.1	15.8	15.5	15.2	16.1	16.1	16.0	16.0			
20.0	14.0	13.9	13.6	13.4	13.1	12.8	13.9	13.8	13.5	13.3	13.0	12.7	13.8	13.7	13.4	13.2			
22.0	12.0	11.9	11.6	11.4	11.1	10.9	11.9	11.8	11.5	11.3	11.0	10.8	11.8	11.7	11.4	11.2			
24.0	10.4	10.3	10.0	9.8	9.5	9.3	10.3	10.2	9.9	9.7	9.4	9.2	10.2	10.1	9.8	9.6			
26.0	9.0	8.9	8.6	8.4	8.1	7.9	8.9	8.8	8.5	8.3	8.0	7.8	8.8	8.7	8.4	8.2			
28.0	7.9	7.8	7.5	7.4	7.0	6.7	7.8	7.7	7.4	7.3	6.9	6.7	7.7	7.6	7.3	7.1			
30.0	6.9	6.7	6.4	6.2	5.9	5.6	6.8	6.7	6.4	6.2	5.8	5.6	6.5	6.4	6.1	5.9			
32.0	5.8	5.7	5.4	5.2	4.8	4.6	5.8	5.7	5.3	5.2	4.8	4.6	5.5	5.4	5.0	4.8			
34.0	4.9	4.8	4.5	4.3	3.9	3.7	4.9	4.8	4.4	4.3	3.9	3.7	4.6	4.5	4.1	4.0			
36.0	4.1	4.0	3.7	3.5	3.1		4.1	4.0	3.6	3.5	3.1		3.8	3.7	3.3	3.2			
38.0	3.4	3.3	3.0				3.4	3.3	2.9				3.1	3.0					
40.0	2.8	2.7					2.7	2.6											

- 【注意事項】
1. 本表に示す定格総荷重は水平堅土上における値で転倒荷重の78%以内および移動式クレーン構造規格で定める前方安定度が1.15以上の両方を満足する値です。
  2. 実際に吊り上げ得る荷重は上表の値からフック(主フック)、玉掛けロープ等吊り具一切の重量を差し引いた値となります。
  3. 各補助ジブは、補フック付きです。
  4. 作業を行う場合は必ず、ハイマストにしてください。
  5. 本表はカウンターウエイト重量43.7tの場合です。